

MOSES Instrument and Data Inversion


CHARLES KANKELBORG, J. LEWIS FOX

Physics Department, Montana State University

THOMAS R. METCALF

Lockheed-Martin Solar and Astrophysics Laboratory

MSSL *Solar Orbiter* Imager — 2003 Oct 16




Outline — Instrument




- *MOSES* instrument concept
- Rocket instrument
- Benefits and costs
- Design approach for *Solar Orbiter*
- Specific design possibilities
- Conclusions


MOSES—Multi-Order Solar EUV Spectrograph



Rocket Instrument



1. Flight hardware complete—February, 2004
2. Calibration, I&T—Spring, 2004
3. Flight—Summer, 2004



Benefits and Costs




Benefits:

- Speed (100 – 1000× comparable slit spectrograph)
- Simultaneity (no scanning in space or spectrum)

Costs:


- Detector real estate
- Inversion



Design Approach for Orbiter



1. Establish constraints (telemetry, volume, mass)
2. Choose lines and parameters to measure
3. Choose orders and dispersion
4. Verify inversion
5. Iterate & optimize




Design Possibilities



- Gregorian layout
 - Magnification (compactness)
 - Field stop (edge effects, spectral selectivity)
 - TVLS gratings (Poletto & Thomas 2003)
- Multiple orders per detector
 - More spectral parameters, less ambiguity
 - Trade off: more detectors, or multiple orders per detector


Example: 4 k \times 4 k detector, 75 km pixels, 4 orders, 150,000 km FOV (leaving 96 pixel margin between orders).



Conclusions




- New capability: simultaneous measurement of spectral parameters in a narrow band, over a large 2D field of view.
- Propose specific observables as a starting point for design (Thanks Ben!)



Inversion—Outline



- Inversion problems in solar physics
- Tomography in hybrid space (x, λ)
- Fourier backprojection
- Pixion reconstruction
- Discussion
- Conclusions
- Next Steps



Inversion




Inversion problems are endemic to remote sensing, and to solar physics in particular:

- *MOSES*
- Differential emission measure
- Coded-aperture imagers (HXT, RHESSI)
- Magnetography

For example, magnetography requires simplifying assumptions about the spectrum in a pixel.


Inversion = Tomography




Fourier Backprojection



- Each projection corresponds to a slice in the Fourier transform of $I(x, \lambda)$.
- Include horizontal projection, $I_\infty(\lambda) = \int I(x, \lambda) dx$
- Iterate to enforce $I(x, \lambda) > 0$.






Characterizing $I_{\infty}(\lambda)$



The inversion relies on knowing $I_{\infty}(\lambda)$, which is not measured directly.

- He II line center can be derived from the data (and the 3 orders co-aligned) by cross-correlation.
- He II line width can be inferred in at least two ways:
 - Knowledge of typical solar values plus instrumental linewidth.
 - Convergence of iteration for non-negativity.
- Si XI contribution does not significantly influence results for He II profile.


Fourier Results




Pixon Reconstruction



- Incomplete fuzzy Pixion basis
- χ^2 goodness of fit
- Fit the data using the least information.
- Include horizontal projection $I_\infty(\lambda)$



Pixon Results




Comparison of results



Differences between true and reconstructed line profile parameters. Line center and linewidth errors are in pixels. For each parameter, a mean offset and RMS error are given. One *MOSES* pixel is approximately 20 mÅ (20 km/s at 304 Å).


Algorithm	center (median)		width (quartiles 1-3)	
	mean	RMS	mean	RMS
Fourier	-0.01	0.32	-0.19	0.97
Pixon	-0.04	0.36	-0.04	0.59

Slit spectrograph




Centroiding error due to Poisson noise only.

MOSES backprojection



The glass is half full: if error is systematic, perhaps it can be corrected.




Conclusions



- Inversion demonstrated by both Fourier and Pixon methods.
- He II is recovered, but not the weaker Si XI.
- Doppler shift reconstructed to $\frac{1}{3}$ -pixel accuracy.
- Linewidth is reconstructed best by pixon (0.6 pixel).
- Exploring several avenues to improve performance.


A paper is in press for *Proc. SPIE*. Preprints available upon request.



Next Steps



- Complete the Pixon algorithm (Fox & Metcalf).
- Parametric forward modeling (Fox).
- Understand and correct systematic errors in reconstruction.
- Quantify benefits of adding more orders (Theissen).
- Simulation/validation of specific wavelength options for *Orbiter* (Dobke).



Acknowledgments



The *MOSES* investigation is sponsored by NASA grant NAG5-10997. JLF gratefully acknowledges support from the NASA GSRP program, grant NGT5-50471.