

# The Foil $\TeX$ class package\*

Jim Hafner  
IBM Research Division  
Almaden Research Center, K56-B2  
650 Harry Road  
San Jose, CA 95120-6099  
hafner@almaden.ibm.com

Printed on November 28, 2002

## Preface

The original Foil $\TeX$  was a  $\LaTeX$ -like system for typesetting foils which used its own format file. This new version has converged into a  $\LaTeX 2_{\epsilon}$  class package. Its features include simplicity of use, compatibility with  $\LaTeX$ , large sans serif font as default, extra macros to start foils with bold headings and special mechanisms to control the footer and header. The primary enhancement, besides the gain obtained by being just a class file for  $\LaTeX 2_{\epsilon}$ , is the addition of simple tools to rotate either the entire set of foils to landscape mode or to rotate individual foils. Because this is integrated with  $\LaTeX 2_{\epsilon}$ , the use of color and other fancy stuff comes automatically. No additional utilities are required.

This document is the user guide for Foil $\TeX$  and describes its basic features and components.

There are restrictions on the use of Foil $\TeX$ . Please refer to Section ?? for more information<sup>1</sup>.

$\TeX$  is a trademark of the American Mathematical Society. POSTSCRIPT is a trademark of Adobe Systems, Incorporated.

---

\*This package has version number v2.1.4, last revised 2002/10/17.

<sup>1</sup>Copyright ©1995,1997,1998,2002 by International Business Machines Corporation.

## Contents

This document describes the FoilTeX system (version 2.1.4) for making foils (slides, transparencies, overheads, etc.). In contrast to the previous version which required its own format file, this new version is fully integrated into L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> as a class package. Like the earlier version, it is much simpler to use than S<sub>L</sub>T<sub>E</sub>X (or the S<sub>L</sub>T<sub>E</sub>X class package), and should be very easy for typical L<sup>A</sup>T<sub>E</sub>X users to master. This document tells you about the special features it has and the extra macros that have been added. It also includes installation instructions which are now much easier than version 1.0.1. Other than some differences with font availability (sizes not families), it should work under any implementation of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. It is assumed that you are already familiar with L<sup>A</sup>T<sub>E</sub>X. If not, you should get the books *L<sup>A</sup>T<sub>E</sub>X: A Document Preparation System* 2nd edition, by Leslie Lamport [?], and *The L<sup>A</sup>T<sub>E</sub>X Companion*, by Michel Goossens, Frank Mittelbach and Alexander Samarin [?].

## 1 The FoilTeX package

The FoilTeX package consists of the files listed in Table ?? on top of the basic implementation of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. You will probably get it packaged with just the first three files. The others are generated by running L<sup>A</sup>T<sub>E</sub>X on the `foiltex.ins` file (see Section ?? for more details). Documentation (both user guide and code description) can be obtained by running L<sup>A</sup>T<sub>E</sub>X on the `foiltex.dtx` file.

Table 1: The files in the FoilTeX package

<code>readme.flt</code>	a simple readme file
<code>foiltex.ins</code>	driver file for unpacking
<code>foiltex.dtx</code>	user guide and documented source
<code>foils.cls</code>	main class file
<code>fltfonts.def</code>	font definition file
<code>foils.sty</code>	compatibility mode style file
<code>foil17.clo</code>	17pt class option file
<code>foil20.clo</code>	20pt class option file
<code>foil25.clo</code>	25pt class option file
<code>foil30.clo</code>	30pt class option file
<code>foilshrt.clo</code>	shortform class option file (new in 2.1.3)
<code>sampfoil.tex</code>	sample FoilTeX file

The main class file, `foils.cls`, together with `fltfonts.def` form the heart of FoilTeX. The former defines the basic set of macros that are used (and includes a request to input the latter) and the latter defines all the fonts used by FoilTeX. Font selection is done via the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> NFSS scheme. The `foils.sty` file is just a wrapper for `foils.cls` in compatibility mode.

The next group of files are the class option files that change the default font sizes and some list spacing parameters. See Sections ?? and ?? for more information about these files.

The last file is a relatively extensive sample file. It demonstrates some of the basic features and is self-documented. If you don't like reading documentation (like this) you can probably do pretty well with FoilTeX simply by browsing through

the sample file and looking at its output. To see its output (after installation), simply type

```
latex sampfoil
```

This creates the `.dvi` and `.aux` files. You will need to rerun this step to get the cross-referencing right. You can then preview or print this as you would any other `.dvi` file.

## 1.1 Package differences with original Foil $\TeX$

The original Foil $\TeX$  package (version 1.0.1) contained a number of similar files plus many more. Because Foil $\TeX$  is now integrated with  $\LaTeX$ , the additional files are no longer necessary. For example, we no longer include the `colordvi.sty` files since this is handled in a much cleaner and more integrated way with the `color.sty` of the `graphics` package. We also don't include anything for POSTSCRIPT fonts since that is nicely handled with the PSNFSS packages. Because we are integrated with  $\LaTeX$ , you can even use the `t1enc.sty` package to access the EC fonts (see below). (This has not been extensively tested because the author doesn't use them, but it did work on some smaller test cases, e.g., `sampfoil.tex`.) There are no more system-specific files since that is handled directly by the  $\LaTeX$  installation. Similarly, we don't need to include a file for using the  $\mathcal{M}\mathcal{S}\text{-}\TeX$  fonts. Finally, the “This is *not*  $\LaTeX$ ” warning has been removed as it is completely irrelevant now.

## 1.2 Additional Features in Version 2.1

There are very few new features in this version. The biggest change is the support for the new EC fonts (and backlevel support for the DC fonts version 1.3 which was not included in version 2.0.1 of Foil $\TeX$ ). An alternative to the `t1enc.sty` package for accessing the EC fonts (with the T1 encoding) is via the line

```
\usepackage[T1]{fontenc}
```

in the preamble. See Section ?? for more information about using these fonts. Note, that we have no support for the TC ( $\TeX$  Companion) fonts, since we don't understand how they are used.

The only other changes are either small bug fixes (most notably with the footnote — thanks to Angelika Schneider for finding two!) and a re-encoding of the `fltfonts.def` file so that it is smaller. Version 2.1.1 has a small bug fix to the order of list environment definitions.

## 1.3 Additional Features in Version 2.1.3

Version 2.1.2 probably never made it outside of IBM, but it included a number of other bug fixes. Version 2.1.3 has the following additional features:

- Addition of a `\captionfraction` command to set the width of the captions as a fraction of the text width. With these, we have deprecated `\captionwidth`. See Section ?. This was found by John Wu.
- Rotation support for DVIPSONE from Y&Y, Inc. My thanks to them for passing on the necessary code changes.

- Addition of `shortform` class option, which can be used to generate a document which takes up much less space (paper, mostly). This was added in response to some requests by Neal Beck who asked for something like this over a year ago.
- Bug fix for the `figure*` and `table*` and related environments (these were supposed to be unnumbered but always had a number). Thanks to Scott Berger for finding this problem.
- Bug fix for the `\big` and related operators. This bug was reported by Hans-Peter Zehrfeld (thanks).
- Additional support for other paper sizes, as provided by Owen Kelly. These new sizes are `ledgerpaper`, `legalpaper`, `a3paper`, `a2paper`, `a1paper`. The second of these had been suppressed in earlier versions. It is restored here on request.

## 1.4 Additional Features in Version 2.1.4

Version 2.1.4 has the following additional features and fixes:

- Patches to enable rotation with MicroPress'  $\text{V}\text{T}\text{E}\text{X}$ , courtesy of M. Vulis and W. Schmidt, from May 2000.
- New paper (sort of) dimensions for screen display of foils, provided by Stephen Sangwine.
- Enhancements to work with  $\text{PDF}\text{L}\text{A}\text{T}\text{E}\text{X}$ .
- Interoperability patches for `hyperref`.
- A simple mechanism (`fltfonts.cfg` configuration file) to allow for more user-customizable fonts.

Many thanks to all who contributed these patches and fixes and suggestions and my apologies for taking so long to incorporate them.

## 1.5 Related Packages on CTAN

A number of people have contributed to the  $\text{Foil}\text{T}\text{E}\text{X}$  family (in some ways indirectly). For example, check out `epslatex.ps` by Keith Reckdahl which describes a way to put a EPS Logo on every page and still manage to keep the size of the relating PostScript file small (effectively only loading the real EPS logo only once as a header file). You can find this document in the `info` directory on your favorite CTAN.

Another package you can find on CTAN is the `FoilHTML` package by Boris Veytsman. It provides extensions to `latex2html` to handle  $\text{Foil}\text{T}\text{E}\text{X}$ 's extra macros.

If you want to put multiple foils (reduced) on a single page, you can use the `psnup` utility (found in most good  $\text{T}\text{E}\text{X}$  bundles).

## 2 Getting started: the `\documentclass` command

`\documentclass{foils}` To create a Foil $\TeX$  document, you edit a  $\LaTeX$  file. Instead of the standard  $\LaTeX$  options specified in the `\documentclass` command, you should use

```
\documentclass[opts]{foils}
```

Here, the *opts* list can include most of the standard  $\LaTeX$  class file options plus a few more Foil $\TeX$ -specific ones that are documented in Section ??.

`17pt,20pt,25pt,30pt`  
`shortform` By default, `foils.cls` loads `foil20.clo` and sets up the normal size fonts at 20pt. Analogous to  $\LaTeX$ 's `11pt` and `12pt` style options, Foil $\TeX$  has `25pt`, `30pt` and `17pt` options. For example, to make normal size at 25pt the command

```
\documentclass[25pt,opts]{foils}
```

will do the trick. The default `20pt` is an acceptable option, though it is redundant. Besides the `pt`-type options, version 2.1.3 adds the `shortform` option. This can be used instead to create a document which takes up much less space (paper?) and so is suitable for redistribution. The text is sized similar to the `12pt` option of `article.cls`.

Once you have created your Foil $\TeX$  file, run  $\LaTeX$  on it to get your `.dvi` file:

```
latex filename
```

## 3 The basic features

Foil $\TeX$  has a number of (hopefully useful) built-in features. The first is that the basic fonts are in large size, approximately 20pt, (so you do not need to do size changing to get large type). The default font is also `sans serif` as this (in the opinion of many) looks better on foils than serif fonts like `roman`. We have implemented  $\LaTeX$ 's font and font size changing commands relative to this default. More information about fonts and size changing can be found in Section ??.

In spite of the fact that the basic font is `sans serif`, the numerals and other symbols from the `roman` font when used in math mode are still in the `roman` font. Thus mathematics will look exactly the same as in  $\LaTeX$  (only larger) but numerals in text will appear in `sans serif`. This is one of its nicer features.

In addition, almost all  $\LaTeX$  macros are available including automatic referencing and citation, footnotes, and `itemize` (which will probably be very popular for foils). The user is not expected to have to do anything to control font types or size changing, except as might be expected in a typical  $\LaTeX$  document.

`sampfoil.tex` The next subsections describe a number of additional macros and features that have been defined to make foilmaking easier. See the `sampfoil.tex` file for a look at how some of these are used.

### 3.1 The class options

The following standard  $\LaTeX$  class options are *not* supported in Foil $\TeX$  because they don't make sense in this environment:

```
a5paper, b5paper, executivepaper, 10pt, 11pt, 12pt,  
oneside, twoside, openright, openany, titlepage, notitlepage,  
onecolumn, twocolumn.
```

These all default to no-ops and, with the exception of `oneside`, `titlepage` and `onecolumn`, all give a warning message.

The following new options are supported in Foil $\TeX$ .

`35mmSlide`  
`Screen4to3|Screen16to9`  
`headrule`  
`footrule`  
`dvips|dvipsone|vtex`  
`magscalefonts`  
`useDCfonts`  
`*paper`  
`landscape`

`35mmSlide` This sets up the page layout for 7.33in. by 11in. paper, which is about the same aspect ratio as a 35mm slide. You can use this if you plan to reproduce on this medium.

`Screen4to3|Screen16to9` These set up page layout for portrait display but in dimensions suitable for a computer display (without rotation).

`headrule` This places a rule below the header on every page (except the title page).

`footrule` This places a rule above the footer on every page (except the title page). These two items seemed to be in demand and should preclude the use of `fancyheadings.sty` which can collide with some of Foil $\TeX$ 's page layout (see Section ?? for additional information).

`dvips|dvipsone|vtex` In order to support rotated foils and `landscape` in a clean way, we need to issue `\specials` which are driver dependent. Since we only had access to one POSTSCRIPT driver, namely, Rokicki's `dvips`, we could only support these `\specials` for this one driver. Declaring this option enables this special code. The folks at Y&Y, Inc., have passed on the necessary modifications to support their DVIPSONE driver. Since I can't test this, I don't support it, but it's included in case it helps. Foil $\TeX$ 2.1.4 can also generate `\specials` appropriate for use with  $\TeX$  in PDF or POSTSCRIPT mode. These can be accessed with the `vtex` option, but that is *not* required as  $\TeX$  is autodetected. As with DVIPSONE, I have no way to test this, so it is supplied unsupported (by me, anyway). See also Section ?? and Section ??.

`magscalefonts` When using the T1 encoding, use mag-scaled versions of the 10pt fonts (with some exceptions) rather than the large design sizes of the EC (or DC) fonts. This is new in version 2.1 (see Section ??).

`useDCfonts` Foil $\TeX$  now supports the official EC fonts with the T1 encoding. For legacy users, this option will revert back to the last release of the DC fonts (version 1.3). This is new in version 2.1 (see Section ??).

`*paper` We've added support for these other paper sizes for making posters. These are

- `ledgerpaper` at 11in by 17in.
- `legalpaper` at 14in by 8.5in.
- `a3paper` at 420mm by 297mm.
- `a2paper` at 594mm by 420mm.
- `a1paper` at 840mm by 594mm.

`landscape` This adjusts the page dimensions by essentially swapping height and width. Typically, it does not force the driver to do the necessary rotation steps. As mentioned, in Foil $\TeX$  with the `dvips`, `dvipsone` or `vtex` option, both actions are handled automatically.

**Note:** It is *highly* recommended that users place most of the class options in a `foiltex.cfg` file (see Section ??) instead of having them specified in the source file itself (as a class option). This allows for better portability of documents.

### 3.1.1 Default options and `foiltex.cfg`

`foiltex.cfg` The default options for Foil $\TeX$  are `letterpaper,20pt,final`. However, you can have your own set of modified default options for Foil $\TeX$  simply by having in your inputs path a file called `foiltex.cfg` with a line containing `\ExecuteOptions` statements. E.g., to configure for `dvips` and `landscape` and older DC fonts, your `foiltex.cfg` file might look like

```
\ExecuteOptions{dvips,landscape,useDCfonts}
```

This file is not required, but can help set things up either system-wide or just for your personal use.

### 3.1.2 Default fonts and `fltfonts.cfg`

`fltfonts.cfg` The default fonts for Foil $\TeX$  are based on CM or EC/DC fonts and are loaded through the `fltfonts.def` file supplied in the package. However, if you or your  $\TeX$  system are very clever, you can have your own set of preferred fonts. To do this, place a file called `fltfonts.cfg` in your inputs path. Include in this file enough information (e.g., a modified `fltfonts.def` file or instructions to load other font definition files (e.g., `.fd` extensions)) to configure the fonts you like. The `fltfonts.cfg` file is not required, but can help set things up either system-wide or just for your personal use. Note, however, that this mechanism should be used with caution.

### 3.1.3 New Options in Version 2.1

There are two options new to version 2.1. The first is the `magscalefonts`. With the original OT1 font encoding, the large fonts are basically scaled versions of the 10pt CM fonts (with a few exceptions). Using the T1 encoding, the fonts are sized by changing the design point size, not scaling a small font. With the use of the EC fonts in this encoding, the presentation of the foils is *very* different, since scaled versions of small fonts look very different from large point design fonts. The author personally found that these scaled EC fonts looked thin and did not present themselves well. Consequently, declaring this option will replace the large design fonts with scaled versions of the smaller fonts (e.g., the normal font `ecss2074` is replaced by `ecss1000 scaled 2074`). The disadvantage of using this option is that you will need effectively two sets of large EC fonts, the scaled small fonts and the large design fonts. I don't know any other way to deal with this problem. This option has no effect when using the OT1 encoding (which is the default).

The second additional option, `useDCfonts`, is probably temporary (to be removed at a later date). This option will use the (now unsupported?) DC fonts version 1.3 instead of the default EC fonts. This is included as a courtesy for DC font users who are not yet ready to move to the official EC fonts. This also works in conjunction with the `magscalefonts` option with the same reasons and caveats as above. This option has no effect *unless* you do something to change the font encoding to T1.



You can add either or both of these options to your `foiltex.cfg` file as desired (see above).

### 3.1.4 New Options in Version 2.1.3

As mentioned in Section ??, the following options are new in this version: `dvipson`, `shortform`. The first provides rotation support for Y&Y, Inc.'s PostScript driver. This can be put in your `foiltex.cfg` file. The second, as described above, provides a method for generating an output document which uses less paper. This is probably *not* suitable for the configuration file. Also, we've added support for more (larger) paper sizes.

### 3.1.5 New Options in Version 2.1.4

We've added the following new options (described elsewhere) to this release: `Screen4to3`, `Screen16to9`, `vtex` (not needed as this is auto-detected).

## 3.2 The `\maketitle` command

`\maketitle` Foil $\TeX$ 's `\maketitle` command produces results similar to  $\LaTeX$ 's `titlepage` class option. That is, it reads the contents of `\title{}`, `\author{}`, etc., and produces a titlepage, actually a title foil. The title itself appears horizontally centered and down a small space from the top, in a `\Large` bold sans serif font. The author's name with address and date appear under the title, centered and in the `\normalsize` font. If desired, this can be followed by a (necessarily short) abstract with the word "Abstract" appearing in bold and centered above the text of the abstract. The footer of the title page will contain some special text (see Section ?? for more details). The difference with the `titlepage` class option is that the abstract appears on the same page as the title/author information (provided  $\LaTeX$  didn't force a page break).

## 3.3 The `\foilhead` and `\rotatefoilhead` macros

`\foilhead` You start new foils with either the `\foilhead` or `\rotatefoilhead` macros. Their  
`\rotatefoilhead` use is described by the following examples:

```
\foilhead{text}
\foilhead[length]{text}
```

This starts a new page and puts *text* in `\large` bold type at the top center of the new page. After the header, a vertical space is added providing an automatic cushion between the header and the body of the foil. You can adjust this space either up or down by putting in the optional argument a  $\TeX$  *length*. For example, if you want the body of your foil to sit closer to the header, you could use the command

```
\foilhead[-.5in]{This is the Header}
```

The default spacing is equal to the sum of

```
\parskip + \baselineskip + \foilheadskip
```

The dimension `\foilheadskip` is new to FoilTeX v2.1.4 and defaults to `18pt plus 0pt minus 18pt` in normal mode and `.25in` in compatibility mode. You can reset this default using a `\setlength` command.

The new (to FoilTeX v2.1.4) macro `\rotatefoilhead` can be used just like the above. If the `dvips` class option has been declared, then it attempts to rotate the *entire* foil 90 degrees from the default position. This means a couple of things. First, if the default position is portrait, then this foil will be rotated to landscape. If the default position is landscape (by use of the `landscape` option), then it rotates to portrait. A similar thing happens if the `dvipsone` option is enabled.

Furthermore, if L<sup>A</sup>T<sub>E</sub>X decides that it needs to split a rotated foil into more than one page, each of these pages will also be rotated. Normal orientation is recovered by the next invocation of `\foilhead`.

The `lscap` and other package files that can be used to rotate the contents of a page only rotate the page body but leave the header and footer in their normal orientation. This makes sense in documents but not on foils. Consequently, we have to support rotation in a different way. `\rotatefoilhead` will rotate everything on the page.

These macros should be used to start any new foil, especially if a new heading is needed. If you try to put too much text on a single foil, FoilTeX will do its own page break. This could cause some odd vertical spacing since there is a fair amount of stretchability in vertical glue, particularly in list environments. This can easily be fixed simply by forcing a page break with an empty `\foilhead{}` command or a `\newpage` command.

### 3.4 The `\MyLogo` and `\Restriction` macros

`\MyLogo` Another pair of macros not in standard L<sup>A</sup>T<sub>E</sub>X are `\MyLogo` and `\Restriction`. Each takes a single argument and is used to control the contents of part of the footline. By design, the footline consists of the contents of `\MyLogo` followed by the contents of `\Restriction` all left justified, with the page number right justified<sup>2</sup>. On the main foils, the default font size is `\tiny`. The contents of these macros can be an empty box as well. By default, `\Restriction` is empty and `\MyLogo` is the phrase “– Typeset by FoilTeX –”.

The declarations for these macros would normally be placed in the preamble to the document, i.e., before the `\begin{document}` command. However, these macros can be declared or redeclared at any place in the document. They (and all the other commands that control the footer and header) are sensitive to L<sup>A</sup>T<sub>E</sub>X’s output routine. Consequently, care must be taken in their placement to be sure they act on the correct pages. In the preamble or immediately after the `\foilhead` command are best. In addition, there are macro switches that can be used to easily turn on or off the logo, without having to do any redeclarations. See Section ?? for more information.

`\MyLogo` is really intended for something idiosyncratic to the speaker or his organization. For example, if you use the `graphics` or `graphicx` packages of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>, you can put an `\includegraphics` macro in `\MyLogo` to get some graphic as the logo on every page:

```
\MyLogo{\includegraphics[height=1in]{arclogo}}
```

---

<sup>2</sup>For the title foil, there is no page number; `\MyLogo` and `\Restriction` are centered and appear in `\footnotesize` font.

(together with a preamble command `\usepackage{graphicx}`) puts a one inch tall version of the IBM Almaden Research Center logo (in EPS format) in the lower left corner of all the author's foils. `\Restriction` was included in case you want to have each foil identified for a particular audience. For example, at IBM, we have the option of displaying the IBM logo and words like "Confidential". The defaults are set in `foils.cls`.

### 3.4.1 Toggling the logo

`\LogoOff` `\LogoOn` Users of an early IBM version of Foil<sub>TEX</sub> requested an easier mechanism (than undefining/redefining `\MyLogo`) for inhibiting a logo from appearing on selected foils or all foils. We implemented this feature with two switches. These macros are `\LogoOn` and `\LogoOff` and they do exactly what their names imply. If `\LogoOff` appears before the footer is processed by the output routine no logo will appear (as if `\MyLogo{}` were declared). This stays in effect until `\LogoOn` is encountered, at which point the contents of `\MyLogo` are restored.

So, for example, if you do not want the logo to appear at all, you can put the `\LogoOff` command *before* the `\begin{document}` command. If you want the logo only on the title page, then you can put this command *after* the first occurrence of `\foilhead`. You can then turn the logo back on by putting the `\LogoOn` command in a convenient place.

## 3.5 The other three corners of the page

`\rightfooter` `\lefthead` `\righthead` Since the macros `\Restriction` and `\MyLogo` control the bottom left corner of the page, there are other macros for putting text in the other three corners. These are, not surprisingly,

```
\rightfooter{text}
\lefthead{text}
\righthead{text}
```

They each take one argument, the text you want to place in the associated corner of the page. These can also be redeclared within the document with the appropriate attention paid to the output routine. See Section ??.

By default the headers are empty and the lower right footer is just the page number:

```
\righthead{}
\lefthead{}
\rightfooter{\quad\textsf{\thepage}}
```

except on the title page where they are all suppressed. You can easily suppress page numbering by declaring `\rightfooter{}`. Unless controlled by a font size changing command, text in these regions appear in a `\tiny` font. These defaults are set in `foils.cls`

## 3.6 Header and footer rules and fancyheadings.sty

Many users requested a simple utility for putting rulers in the header or footer. As mentioned above in Section ??, this is now easily obtained with the `headrule` and `footrule` class options.

`\headwidth` Some users prefer to use the `fancyheadings.sty` package to control their headers and footers. This allows control of rules, as well as centered text in these areas (which we thought was too much clutter). To get `fancyheadings.sty` to work correctly with FoilT<sub>E</sub>X's page rotation mechanism, add the following to your preamble:

```
\let\headwidth\textwidth
```

### 3.7 Predefined Theorem and Proof environments

`\newtheorem` There are a number of (both starred and unstarred) `\newtheorem` environments built in. These are for `Theorem`, `Lemma`, `Corollary`, `Proposition` and `Definition`. Note the uppercased first letter (to avoid possible collisions with user-defined environments of this type). Each must begin and end with `\begin{}` and `\end{}` commands as usual. Their text begins with a bold sans serif label like **Theorem** and the content of each is typeset in *slanted sans serif*. The unstarred forms are sequentially numbered and support automatic referencing. The starred forms suppress the numbering and referencing.

All these environments also support an optional argument that can be used for the inventor, common name of the theorem, etc.. Thus

```
\begin{Theorem*}[Gauss] Quadratic reciprocity is true!
\end{Theorem*}
```

will produce (in large type)

**Theorem. [Gauss]** *Quadratic reciprocity is true!*

The unstarred form will be numbered.

To implement this, we added code to L<sup>A</sup>T<sub>E</sub>X's `\newtheorem` macro which defines *both* the starred and unstarred forms of these environments at the same time. In this way, users could easily add their own versions of similar environments. For example,

```
\newtheorem{Axiom}{Axiom}
```

would define two environments `Axiom` and `Axiom*` that behaved just like `Theorem` and `Theorem*`. In all other respects, e.g., numbering convention, `\newtheorem` behaves just as in L<sup>A</sup>T<sub>E</sub>X.

Finally, there is a `Proof` environment which opens with the word **Proof** and ends with a  $\square$ . The contents are printed in the normal font.

### 3.8 Mathematics in bold typeface

`\bm` Because FoilT<sub>E</sub>X is fully integrated into L<sup>A</sup>T<sub>E</sub>X, getting bold math is pretty much the same. The only thing we did was to add some extra facilities to get at it. The first we add is the `\bm` macro which takes one argument:

```
\bm{formula}
```

This takes its argument (within mathematics mode) and replaces it with its emboldened version. This is different from the `\mathbf` command in that it emboldens everything including symbols. The new version of this (as opposed to `FoilTeX` v 1.0.1) is much better. It deals correctly with the current math style and so should work even in superscripts!

`boldequation` The second method for getting bold mathematics is a pair of environments:

```

\begin{boldequation}
formula
\end{boldequation}

\begin{boldequation*}
formula
\end{boldequation*}

```

They both set *formula* in bold (even super- and subscripts). The unstarred form has automatic referencing and is numbered; the starred form inhibits the numbering and referencing. Essentially, they just do an automatic `\boldmath` at the beginning and an `\unboldmath` at the end of the formula.

### 3.9 Hyphenation and raggedright

`\righthyphenmin` `FoilTeX` turns off hyphenation but allows a fair amount of horizontal interword spacing. Unfortunately, this can create some unpleasant line breaks (at times).  
`\lefthyphenmin` This can be fixed with either a manual fill and line break (I use `\hfil\break` but that's very `TeXy`) or by inserting a discretionary hyphen (better to have them only when needed than to have them happen unpredictably).  
`\raggedright`

Some users feel that `\raggedright` is preferable for foils. It was decided not to make this the default (as this is not the author's opinion), but to leave this to the user's discretion. To get this effect, simply put `\raggedright` in the preamble to your document. This will also reduce the spacing problems.

We turned off hyphenation by setting `\righthyphenmin` and `\lefthyphenmin` each to 100. Resetting this to smaller numbers (less than the length of typical words) will restart hyphenation. (This is an improvement over version 1.0.1, where we didn't even load the hyphenation tables into the format.)

### 3.10 Non-floating floats

`figure` Many people like to use figures and tables in their foils and typically want to use  
`table` them with the same interface as they do in documents (namely, using the `figure` and `table` environments). Unfortunately, in standard `LATeX` these are "floats" which means they can appear on some place other than their current spot. This, of course, makes no sense on foils. To alleviate this, we define these environments but as non-floats. The user syntax is identical to standard `LATeX`, but a couple of things happen. First, the placement parameters are completely ignored. Second, they don't float (equivalent to [H] placement). Third, there is no "List of Figures" or "List of Tables" data generated. The only other difference is that the starred forms of these environments are unnumbered (as opposed to being one-column in a two-column document).

`\newnonfloat` We have added a simple mechanism for the user to add their own version of

these non-floats. This is done with the `\newnonfloat` mechanism. For example, the `figure` and `figure*` (unnumbered) environments of `FoilTeX` are defined with:

```
\newnonfloat{figure}{Figure}
```

### 3.11 User adjustable dimensions

```
\foilheadskip
\abovefloatskip
\captionfraction
\abovetitleskip
\titleauthorskip
\authorauthorskip
\authordateskip
\dateabstractskip
```

There are a number of new dimensions added to `FoilTeX` which the user can adjust as they desire. One, `\foilheadskip` has already been mentioned.

For controlling the space around floats there are a number of dimensions. First, there are the two predefined in `LATEX`, namely, `\abovecaptionskip` and `\belowcaptionskip`. Next, we added one (`\abovefloatskip`) for the space above the non-float. See the code for default settings for these skips. Finally, in version 2.1.2 we added a `\captionfraction` command to set the width of the captions as a fraction of the text width. Implementation is similar to `LATEX`'s fractions for floats, so that it should be reset with the `\renewcommand`. The default value is 1.0. Releases of `FoilTeX` before version 2.1.2 allowed the user to set the caption width with the dimension `\captionwidth`. This was buggy and behaved badly under rotations and landscape and so has been deprecated.

For the titlepage, between every single vertical item there is some extra space. These spaces can take up a lot of room and if you have a lot of authors or a long title or a long abstract and can't get everything you want on the page, adjust these parameters as needed:

```
\abovetitleskip, \titleauthorskip, \authorauthorskip,
\authordateskip, \dateabstractskip
```

```
\zerolistvertdimens
```

Furthermore, there is a new declaration called `\zerolistvertdimens`. You can use this *inside* a list environment to shrink all the vertical spacing to a minimum.

### 3.12 Differences with `LATEX`

```
\em
\emph
```

One simple difference is that the `LATEX` commands `\em` and `\emph` switch from any unslanted font to *slanted sans serif* and from any slanted font to *unslanted sans serif*, not to *text italics* and *roman*, respectively.

Unlike `TEX/LATEX`, numerals in `FoilTeX` look different when they are in ordinary text from when they are in math-mode. This means that 12345 in text will print as 12345 and  $\$12345\$$  prints as 12345.

### 3.13 Future versions

There are plans for two major additions to `FoilTeX`. These are support for user comments (side notes) and for overlays. There is no time-table for these upgrades. (As one can probably tell, this many take a really long time to do. Or as history has shown, probably won't ever come to be.)

In the meantime, you can play with the `comment` package for side notes and the `color` package (using `white` to hide text) for overlays. For side notes, you can use the comment environment's suppressed mode for the real foils. Then use the `shortform` option and enabled comments to generate the side note foils. The foils will layout very differently, but the content will be there.

Foil $\TeX$  should be able to handle rotation and landscape with other dvi drivers. This will be added only with user assistance because the author has no way to test other drivers.

## 4 Fonts and their sizes

As noted earlier, the default font at `\normalsize` is a **sans serif** font at size 20pt, unless one of the `[17pt]`, `[25pt]`, `[30pt]` or `shortform` options have been declared in the `\documentclass` command. Table ?? shows the control sequences for other accessible text fonts and the name of the font in a sample of its type. These control sequences give the font at the current size. Font size changing commands for each of the normal point size options are described by Table ??. Note that `\bf` and `\sl` yield sans serif fonts, not the usual variations on roman.

Table 2: Available fonts and their names.

command	font names
<code>\sf</code>	Sans Serif
<code>\it</code>	<i>Text Italic</i>
<code>\sl</code>	<i>Slanted Sans Serif</i>
<code>\bf</code>	<b>Bold Sans Serif</b>
<code>\tt</code>	Typewriter
<code>\rm</code>	Roman
<code>\sc</code>	SMALL CAPS

Table 3: Type sizes for Foil $\TeX$  size-changing commands for the different document style options. In compatibility mode, the largest size is 43pt.

size	doc-options				
	20pt	17pt	25pt	30pt	shortform
<code>\tiny</code>	12pt	12pt	12pt	14pt	12pt
<code>\scriptsize</code>	12pt	12pt	14pt	17pt	12pt
<code>\footnotesize</code>	14pt	12pt	17pt	20pt	12pt
<code>\small</code>	17pt	14pt	20pt	25pt	12pt
<code>\normalsize</code>	20pt	17pt	25pt	30pt	12pt
<code>\large</code>	25pt	20pt	30pt	36pt	14pt
<code>\Large</code>	30pt	25pt	36pt	43pt	17pt
<code>\LARGE</code>	36pt	30pt	43pt	51pt	20pt
<code>\huge</code>	43pt	36pt	51pt	51pt	25pt
<code>\Huge</code>	51pt	43pt	51pt	51pt	25pt

There are also the corresponding `\textsf` and related macros. These will work as expected, namely they switch the corresponding font characteristic based on the *current* font.

Table 4: Mathematics type styles and their point sizes at `\normalsize` for the different document style options.

	doc-options				
style	20pt	17pt	25pt	30pt	shortform
<i>displaystyle, textstyle</i>	20pt	17pt	25pt	30pt	12pt
<i>scriptstyle</i>	14pt	12pt	17pt	20pt	12pt
<i>scriptscriptstyle</i>	12pt	12pt	14pt	17pt	12pt

Mathematics is also automatically displayed at normal size unless magnified by a size changing declaration. Table ?? describes the font point sizes for  $\TeX$ 's mathematics styles at each of the normal point size options.

In the previous version of Foil $\TeX$ , we loaded the  $\LaTeX$  circle and line fonts at `\magstep4`. This had the advantage that the lines were thicker and some pictures would scale nicely to foils. Unfortunately, this seems to have created as many problems as it solved. Consequently, in the new version, these fonts are not scaled except in compatibility mode.

## 5 Making color foils

Because color has now been integrated into  $\LaTeX$  itself, we don't add much of anything for color support. Users are encouraged to use the `color` package of the `graphics` package. We no longer recommend the `colordvi` style file that came with the old Foil $\TeX$  and still comes as part of Rokicki's `dvips`. In general it will work OK, but there will be some minor problems that crop up.

We have added just enough compatibility mode to the new Foil $\TeX$  so that old files which use `colordvi` should still run correctly.

## 6 Using POSTSCRIPT fonts

There is not much to say here since the PSNFSS packages do a nice job of things. The only thing to remember is that the default font family is the `\sfdefault` so that using a package that only changes the `\rmdefault` won't help you much. Using a package like `times.sty` will change the `\sfdefault` to Helvetica and *not* to Times-Roman as you might expect. To get your foils (mostly) into Times-Roman, just say

```
\renewcommand{\sfdefault}{ptm}
```

somewhere in the preamble.

## 7 Installing Foil $\TeX$

To install Foil $\TeX$ , simply run  $\LaTeX$  on the `foiltex.ins` file and then follow the instructions at the end. Essentially, just copy the generated files to the appropriate location in your  $\TeX$  inputs, examples and doc trees.



## 8 Usage restrictions

### 8.1 Experimental Software Disclaimer

This program is provided free of charge on an “AS IS” basis without warranty of any kind, either expressed or implied, including but not limited to implied warranties of merchantability and fitness for a particular purpose. IBM does not warrant that the functions contained in this program will meet the user’s requirements or that the operation of this program will be uninterrupted or error-free. You are solely responsible for determining the appropriateness of using this program and assume all risks associated with its use, including but not limited to the risks of program errors, damage to or the loss of data, programs or equipment, and unavailability or interruption of operations.

Acceptance and use of this program constitutes the user’s understanding that he/she will have no recourse to IBM for any actual or consequential damages, including, but not limited to, lost profits or savings, arising out of the use or inability to use this program, or any damages claimed by you based on a third party claim. Even if the user informs IBM of the possibility of such damages, IBM expects the user of this program to accept the risk of any harm arising out of the use of this program, or the user shall not attempt to use this program for any purpose.

### 8.2 User Agreement

BY ACCEPTANCE AND USE OF THIS PROGRAM THE USER AGREES TO THE FOLLOWING:

- a. The user is granted permission to copy this program to the extent reasonably required for such use. This program may be redistributed on a not-for-profit basis, as long as WARRANTY DISCLAIMER, this USER AGREEMENT, and the copyright notice are included with the program.
- b. All title, ownership and rights to this program and any copies remain with IBM, irrespective of the ownership of the media on which the program resides.
- c. The user is permitted to create derivative works to this program. However, all copies of the program and its derivative works must contain the IBM copyright notice, the WARRANTY DISCLAIMER and this USER AGREEMENT. Furthermore, the user must document and initial within the program all changes he/she makes.
- d. By furnishing this program to the user, IBM does *not* grant either directly or by implication, estoppel, or otherwise any license under any patents, patent applications, trademarks, copyrights or other rights belonging to IBM or to any third party, except as expressly provided herein.
- e. The user understands and agrees that this program, and any derivative works made from this program, are not to be sold for profit or commercially exploited in any manner. However, this use restriction shall not operate to deny the right to redistribute the program on a not-for-profit basis, as provided in paragraph ??, above.

- f. IBM requests that the user supply to IBM a copy of any changes, enhancements, or derivative works which the user may create. The user grants to IBM and its subsidiaries an irrevocable, nonexclusive, worldwide and royalty-free license to use, execute, reproduce, display, perform, prepare derivative works based upon, and distribute, (INTERNALLY AND EXTERNALLY) copies of any and all such materials and derivative works thereof, and to sublicense others to do any, some or all of the foregoing, (including supporting documentation).

## 9 Acknowledgements, requests and help

For the first release of Foil $\TeX$ , we had the following acknowledgement:

We would like to thank and acknowledge the following people in IBM for their great assistance in helping to put Foil $\TeX$  together: Katherine Hitchcock, Myron Flickner, Ekkehard Blanz, Melanie Fulgham, Peter Haas, Rocky Bernstein and the many users who contributed their constructive comments on the early test versions within IBM.

A special thanks goes to Tomas Rokicki for implementing our color setup in his driver and another to Sheri Gish of IBM for asking the right (or was it wrong?) question that got this project started.

We echo that acknowledgement again because there would not be a version 2.0 or later without the first release and their help. But, putting together this new release required a new team of helpers. Mostly, I want to thank the  $\LaTeX$ 3 team for doing such a great job with  $\LaTeX$  2 $\epsilon$ . Implementing much of Foil $\TeX$  was greatly eased by the way  $\LaTeX$  2 $\epsilon$  is constructed and implemented.

Beyond this, the  $\LaTeX$  2 $\epsilon$  team was very helpful in a number of discussions about design issues for Foil $\TeX$ , particularly on font issues but also on a number of others. Let me single out the following for exceptional service beyond the call: David Carlisle, Sebastian Rahtz, Frank Mittelbach and Alan Jeffrey.

I also want to thank all the many users who have expressed their interest in Foil $\TeX$  and who have made suggestions, comments, pointed out the bugs and provided fixes.

A special thanks to the folks at Y&Y, Inc., including Louis Vosloo, for providing the stuff needed for landscaping with DVIPSONE.

Similar special thanks to the folks at Micropress, Inc., specifically Michael Vulis and Walter Schmidt for the stuff needed to work with V $\TeX$ .

The following contributed suggestions and code snippets that are if not in fact at least in spirit including in this release: Hans Fredrik Nordhaug, Heiko Oberdiek, Stephen Sangwine, Thomas Sailer, Drew Ronnenberg. Their contributions are gratefully acknowledged.

Foil $\TeX$  is intended to be easy to use, useful and to produce beautiful foils. Consequently, the author welcomes any comments or suggestions.

The author also requests help in supporting landscape and rotation with other drivers. If you find a solution, please pass it back to the author for incorporation in future updates of Foil $\TeX$ .

If you have a question that you can't answer by reading *both* this document and [?, ?], or by posting your question to your local  $\TeX$ pers or to the usual forums, you can contact the author.

## 10 A sample file

In this section we give a complete and self-annotated sample file. We try in this sample to demonstrate or comment on most of the basic features and show how the fonts look in FoilTeX. More details can be found in the sections above.

```
1 (*sample)
2 %%% Everything above this sentence is relevant only to this %%%
3 %%% sample and should not be included in your foils document. %%%
4 % Start with a \documentclass declaration. The [20pt] is optional
5 % as that is the default. The [dvips] option is supplied here even
6 % though it really belongs in the {foiltex.cfg} file for the site/user.
7 \documentclass[20pt,dvips]{foils}
8 %
9 % An alternate uses smaller fonts, passes the draft mode to other
10 % included packages (e.g., graphics packages) and does everything
11 % in landscape mode.
12 % \documentclass[17pt,draft,landscape]{foils}
13 %
14 % This next version declares the setup for Rokicki's dvips so that we
15 % can support rotated foils and the use of color names.
16 %\documentclass[20pt,dvips]{foils}
17 %
18 % Add other packages you might want to use here. E.g., you can
19 % use the \usepackage{graphics} or \usepackage{graphicx} to include
20 % figures (e.g., postscript figures) or \usepackage{color} for color.
21 % See the \FoilTeX documentation for use of color.
22 % \usepackage{graphicx}
23 % \usepackage[usenames]{color}
24 % Use this package file for the special \LaTeX symbols.
25 %
26 \usepackage{latexsym}
27 %
28 % Declare the title, author and date as you would in regular \LaTeX.
29 %
30 \title{A Sample Foils Document}
31 %
32 \author{Jim Hafner\
33         IBM Research Division\
34         Almaden Research Center\
35         \texttt{hafner@almaden.ibm.com}
36        }
37 % This is optional
38 \date{\today}
39 %
40 % We set up the header and footer information now. \Restriction is
41 % always placed next to \MyLogo on the bottom left corner of the
42 % page. The other macros have their obvious placement. If you want
43 % nothing, leave the contents of these declarations empty. Note that
44 % '-- Typeset by FoilTeX --' logo will print automatically, unless
45 % controlled by redefining \MyLogo or by using the switches \LogoOn
46 % and \LogoOff.
47 %
48 %\MyLogo{-- Typeset by \FoilTeX\ --} % this is the default
49 %\rightfooter{quad\textsf{\thepage}} % this is the default
```

```

50 \leftheader{Jim Hafner}
51 \righthead{\foiltexdate} % \foiltexdate is defined above
52 \Restriction{Is this for a restricted audience?}
53 %
54 \newcommand\bs{\char '134} % a backslash character for the \tt font
55 %
56 % Now we can begin the document. The first thing is the title page
57 % on which we might put a VERY short abstract.
58 \begin{document}
59 \maketitle
60 %
61 \begin{abstract}
62 This is where an abstract might go if you want one. There is usually
63 not a lot of room for much here.
64 \end{abstract}
65 %
66 % Now we can begin to start the individual foils. Note that we let
67 % \LaTeX split the pages and don't force each foil to be a separate
68 % page. We use \foilhead to start a new foil or foil topic.
69 \foilhead{Colors}
70
71 \FoilTeX\ (version 2) is fully integrated with \LaTeXe\ so that the
72 supported \texttt{color} package (part of the \texttt{graphics}
73 package) is the preferred way to use colors.
74
75 For examples, see the \texttt{graphics} package documentation.
76
77 You can still use the old \texttt{colordvi} package that comes with
78 Rokicki's \texttt{dvips}, but some things won't work exactly as
79 expected (except in compatibility mode).
80
81 \foilhead[-.5in]{Itemize}
82 \LogoOff % We decided to turn the logo off on this page.
83 % The rest of the footer and header will stay the same.
84 % This foil has a lot on it so we used the [-.5in] option to move the
85 % body of the foil closer to the foilhead. We could move it down with
86 % a positive length.
87 %
88 % By default there is large item separation at the first level (equal
89 % to \parsep). At the lower levels, it decreases to 0. To change
90 % you can either try to redefine \@listii and \@listiii in a style
91 % file or you can change it internally to an item list. See comment
92 % below at second level.
93
94 \begin{itemize}
95 \item
96 This is the first level of an itemize.
97 \begin{itemize} % \itemsep 20pt % this stretches the space
98 % between items but only at this level. We leave
99 % the default here.
100 \item Here we jump to second level
101 \begin{itemize}
102 \item Even third level (and there is a fourth level as well).
103 \item The second item at third level.

```

```

104     \end{itemize}
105     \item The second item at second level.
106     \item A third item at second level.
107     \end{itemize}
108 \item The second item at first level.
109 \item A third item at first level.
110 \end{itemize}
111
112 Note that we have turned off the logo on this page.  It returns on the
113 next page.
114
115 \foilhead{}
116 \LogoOn
117
118 This should be a \emph{new foil} with no header, followed by a quote:
119 \begin{quote}
120 \ldots it's a good idea to make your input file as easy to
121 read as possible.
122 \end{quote}
123 and some enumerating:
124 \begin{enumerate}
125 \item this is enumerated
126 \item this is also enumerated
127 \end{enumerate}
128
129 \begin{center}
130 \framebox{\parbox{5.5in}{Above, we used \texttt{\bs emph\{new foil\}}
131 instead of the old \texttt{\{\bs em new foil\bs/\}}!}}
132 \end{center}
133
134 On the following page we decided to stop the headers from appearing
135 and move the date to the footline.
136
137 % Here are more samples of font actions, particularly size changing.
138 % We retained the ability to get a true Roman font via \textrm.
139
140 \foilhead{Fonts}
141 \righthead{} % These cancel the headlines from now on
142 \lefthead{} %
143 \rightfooter{\foiltexdate\quad\textsf{\thepage}}
144
145 \begin{itemize}
146 \item This shows \textit{italics}, \textsl{slanted}, \textbf{boldface},
147 \texttt{typewriter}, \textrm{roman}, and \textsc{small caps}.
148 \item Unslanted \emph{emphasize} and
149     \textsl{slanted \emph{emphasize}}.
150 \item \texttt{\bs textrm} means \textrm{roman} and
151     \texttt{\bs textsf} means \textsf{sans serif}.
152 \item size changing from {\tiny tiny},
153     {\scriptsize scriptsize},
154     {\footnotesize footnotesize},
155     {\small small}, {\normalsize
156     normalsize},\,{\large large},\,
157     {\Large Large},\,{\LARGE LARGE},

```

```

158     {\huge huge}, and {\Huge Huge}.
159 \item 12pt is the smallest preloaded.
160 \item 43pt is the largest preloaded in compatibility mode.
161 \item 51pt is the largest preloaded in normal mode.
162 \end{itemize}
163
164 \foilhead{Special Characters and Accents}
165
166 \begin{itemize}
167 \item Here is a list of accents:
168   \begin{itemize}
169     \item \'{o}, \'{}{o}, \^{o}, \~{o}, \_{}{o}, \={o}, \.{}{o}, \u{}{o},
170       \v{}{o}, \H{}{o}, \t{}{oo}, \c{}{o}, \d{}{o}, \b{}{o}.
171   \end{itemize}
172 \item First in paragraph mode (with \verb|\copyright|):
173   \begin{itemize}
174     \item \dag, \ddag, \S, \P, \pounds, 0123456789, \copyright
175   \end{itemize}
176 \item Then in math mode: (numerals are different!)
177   \begin{itemize}
178     \item $\dag$, $\ddag$, $\S$, $\P$, $\pounds$,
179       $0123456789$
180   \end{itemize}
181 \item Here are more non-english language symbols:
182   \begin{itemize}
183     \item \oe, \OE, \ae, \AE, \aa, \AA, \o, \O, \l, \L, \ss, ?', !'
184   \end{itemize}
185 \item \textrm{\TeX}'s special symbols: \#, \$, \%, \&, \_, \{, \}.
186 \end{itemize}
187
188 \foilhead{Some Mathematics}
189
190 $$
191 {\cal F}\cdots\frac{x+y}{1+\frac{y}{z+1}}=\sqrt{x+y}\times\sqrt[n]{2}
192 $$
193
194 Here are some funny math symbols (we needed the \texttt{latexsym}
195 package for a couple of these):
196 $$
197 \forall\exists\flat\natural\sharp\partial\angle\Re\mho\jmath\aleph
198 $$
199 $$
200 \infty\Diamond\clubsuit\diamondsuit\spadesuit\heartsuit\ell
201 $$
202 $$
203 \bigcap\bigcup\bigvee\bigwedge\bigodot\bigotimes\bigoplus\biguplus
204 \sum\prod\coprod\int\oint
205 $$
206 $$
207 \sum_{i=1}^n x_i = \int_0^1 f[x]dx.
208 $$
209 and $\gcd(m,n)$ and $x\equiv y\pmod{a+b}$.
210
211 \foilhead{More Math: arrays}

```

```

212
213 $$
214 \begin{array}{clcr}
215 a+b+c & & uv & & x-y & & 27 \\ \
216 a+b & & u+v & & z & & 134 \\ \
217 a & & 3u+vw & & xyz & & 2,978
218 \end{array}
219 $$
220
221 $$
222 \left( \begin{array}{c}
223 \left| \begin{array}{cc}
224 x_{11} & x_{12} \\ \
225 x_{21} & x_{22}
226 \end{array}
227 \right| \\ \
228 y \\ \
229 z
230 \end{array}
231 \right)
232 $$
233
234 $$
235 x=\left\{ \begin{array}{l}
236 y & \mbox{if } y>0 \\ \
237 z+y & \mbox{otherwise}
238 \end{array}
239 \right.
240 $$
241
242 \foiled{More Math: \texttt{equation} and \texttt{array} Numbering}
243
244 Here is a numbered equation
245 \begin{equation}
246 E=mc^2
247 \end{equation}
248 and a numbered array
249 \begin{eqnarray}
250 x & = & 17y \\ \
251 y & > & a+b+c+d+e+f+\nonumber \\ \
252 & & k+l+m+n+o+p
253 \end{eqnarray}
254
255 More math accents:  $\hat{a}$ ,  $\check{a}$ ,  $\breve{a}$ ,  $\acute{a}$ ,
256  $\grave{a}$ ,  $\tilde{a}$ ,  $\bar{a}$ ,  $\vec{a}$ ,  $\dot{a}$ ,  $\ddot{a}$ .
257
258 Over and underline:
259 $$
260 \overline{\overline{x}^2 + 1}
261 \quad
262 \overbrace{a+\underbrace{b+c}_{25}+d}^{16\alpha}
263 $$
264
265 \foiled{Bold Mathematics}

```

266

267 The `\verb|boldequation|` environment, with

268 numbering yields

269 `\begin{boldequation} \label{eq:bold}`

270  $2\sqrt{x} \ \Pi^y \ \sim \pi \times x$

271 `\end{boldequation}`

272 and without numbering yields

273 `\begin{boldequation*}`

274  $2\sqrt{x} \ \Pi^y \ \sim \pi \times x$

275 `\end{boldequation*}`

276 We can reference bold equations like (`\ref{eq:bold}`).

277

278 There is also `\verb|\mathbf|` and `\verb|\bm|` in the middle of a formula,

279 with `\hfil\break \verb|\mathbf{a +} a + \bm{a+x\pi-\rho} -\rho|`

280  $$$$$

281  $\mathbf{a +}a+\mathbf{a+x\pi-\rho} -\rho$

282  $$$$$

283 Note the difference between the two bold ‘a’ in result.

284

285 `\foilhead{Theorem and Proof Environments}`

286

287 `\begin{Theorem}[TUG'92]`

288 There are some `\TeX` tools that are easier to use than others. This

289 theorem is numbered and has an optional acknowledgement.

290 `\end{Theorem}`

291

292 `\begin{Corollary*}`

293 This obvious corollary is not numbered because it uses the `*-form`.

294 `\end{Corollary*}`

295

296 `\begin{Proof}`

297 The details of the proof are left to the reader. Note that the

298 environment names are case sensitive.

299 `\end{Proof}`

300

301 We put a header back on the next foil to see that it is correctly

302 rotated.

303

304 `\rotatefoilhead{Rotated Foils}`

305 `\lefthead{I'm rotated!}`

306

307 This entire page will (should?)~be rotated if we declared the

308 `\verb|\documentclass| option \texttt{dvips}` or other supported driver

309 option. (For `\texttt{pdflatex}`, this works without giving any

310 options!) In the other cases, this is not supported and the user is

311 warned.

312

313 The next foil will return to normal. Only foils that begin with

314 `\verb|\rotatefoilhead|` will be rotated. If `\LaTeX` needs to split a

315 rotated foil into two foils, `\emph{both}` will be rotated.

316

317 `\foilhead{Tables and Figures}`

318 `\lefthead{}`

319



```

320 Here is a short table:
321
322 \begin{table}
323 \begin{center}
324 \begin{tabular}{|l|c|r|} \hline
325 First stuff & Second stuff & Third Stuff \\ \hline\hline
326 foo & bar & bug \\ \hline
327 foofoo & barbar & bugbug \\ \hline
328 \end{tabular}
329 \caption{\label{tab:one}This is the first table.}
330 \end{center}
331 \end{table}
332
333 The above table is Table~\ref{tab:one}. It is a ‘‘nonfloat’’, since
334 it doesn’t float at all, but appears right where it was placed in the
335 document.
336
337 % In the picture environment, we have put the fonts back to \LaTeX’s
338 % normal size. This may have been a mistake but ...
339 \foilhead{\texttt{picture} Environments}
340
341 \begin{figure}
342 \begin{center}
343 \setlength{\unitlength}{.08in}
344 \begin{picture}(50,50)(0,0)
345 %\thicklines % don’t know why it looks worse with this
346 \put(10,35){\framebox(10,10){gnat}}
347 \put(30,20){\circle{20}}
348 \put(30,20){\vector(0,1){2}}
349 \put(45,35){\circle*{5}}
350 \put(30,20){\oval(20,30)}
351 \end{picture}
352 \end{center}
353 \caption{Isn’t this a pretty picture?}
354 \end{figure}
355
356 \verb|\thicklines| would be nice here but the picture doesn’t look as
357 good that way (why?). We should use the \texttt{graphics} package to
358 load our graphics pictures here. Note that this Figure doesn’t float!
359
360 \foilhead{Marginal Notes, Footnotes and Citations}
361
362 A marginal note\footnote{This is a footnote.}
363 is made with the \verb|\marginpar| command, having the
364 text as its argument. The note\marginpar{This is a mar\gin\al note}
365 is placed in the margin, its first line even with the line of the text
366 containing the command\footnote{This is a second footnote.}.
367
368 This is shows \fbox{frameboxes} at work. We can even cite references
369 like \cite{rocky} and \cite{bullwinkle}.
370
371 % We can use any bibliography mechanism, including BibTeX.
372 \begin{thebibliography}{99}
373

```

```

374 \bibitem{rocky} Rocky and Bullwinkle, Open problems, in \textsl{Mr.
375 Know-it-all's Rock Encyclopedia}.
376
377 \bibitem{bullwinkle} Bullwinkle, Getting things out of hats,
378 \textsl{Annals} \textbf{1} (1990BC), 1--2.
379
380 \end{thebibliography}
381
382 \foilhead{Other Features}
383 \raggedright
384
385 \begin{itemize}
386 \item \verb|\raggedright| can be used in the preamble to get this
387     effect throughout as we did on this page.
388 \item Access to the AMS Fonts symbols and Euler fonts can easily be
389     obtained with the \texttt{amsmath} packages. You might not get
390     fonts at the largest sizes however.
391 \item \textsc{PostScript} fonts can used just by adding any of the
392     package files from the PSNFSS package.
393 \end{itemize}
394
395 \end{document}
396 \end{sample}

```

## 11 Description of the code in the Foil $\TeX$ package

In this section we describe the macros used in the package. This is broken up into a number of parts. In the first part we describe the code that sets up and implements the option parsing. This includes the loading of the font definition information and the size option file. Details of the font data itself can be found in Section ???. In the second subsection, we define the basic macros used in Foil $\TeX$ . Subsections ??? have the code for list spacing and list structures. Page layout is described in Subsections ????. The next subsections cover bibliographies (??), non-floating floats (??), foil heads (??), new theorem environments (??), and bold mathematics (??).

### 11.1 The package options

<pre> \if@openbib \if@landscape \if@dvi \if@dvi \if@vtex \if@header@rule \if@footer@rule \if@magscaleECfonts \if@useDCfonts \if@pdftex </pre>	<p>To setup some of the mechanisms for parsing the package options, we need a few conditionals. The first and second conditionals are related to standard <math>\LaTeX</math> document class options. The <code>\if@dvi</code>, <code>if@dvi</code> and <code>if@vtex</code> conditionals, if true, sets up the necessary <code>\specials</code> for page rotation and the like. These are only supported for Rokicki's <code>dvi</code> and provided for Y&amp;Y, Inc's, <code>dvi</code> and MicroPress' <math>\TeX</math>. The two rule conditionals determine if a rule is set in the header and footer, respectively. By default, all of these conditionals are false. The next two deal with how T1 encoded fonts are used. The last is for <code>pdftex</code> detection.</p> <pre> 397 (*package) 398 \newif\if@openbib \@openbibfalse 399 \newif\if@landscape \@landscapefalse 400 \newif\if@dvi \@dvifalse </pre>
---	---

```

401 \newif\if@dvipsonesone \@dvipsonesonefalse
402 \newif\if@vtex \@vtexfalse
403 \ifx\VTexversion\undefined\else\@vtextrue\fi % autodetect
404 \newif\if@header@rule \@header@rulefalse
405 \newif\if@footer@rule \@footer@rulefalse
406 \newif\if@pdftex \@pdftexfalse
407 \newif\if@magscaleECfonts \@magscaleECfontsfalse
408 \newif\if@useDCfonts \@useDCfontsfalse

```

**a4paper** These document class options are used to set the paper layout. Most of these are  
**letterpaper** standard L<sup>A</sup>T<sub>E</sub>X, but a few, namely **35mmSlide**, **Screen4to3** and **Screen16to9**, are  
**35mmSlide** new to Foil<sub>E</sub>X. The first sets the paper dimensions in the aspect ratio for 35mm  
**Screen4to3** film, namely, 2 × 3 and just big enough to fit on US letter paper (I'd have picked  
**Screen16to9** A4 paper, but I'm US centric!). The next two, set them to relative dimensions for  
**landscape** full screen displays at ratios 4x3 and 16x9. These are already rotated for displays  
**ledgerpaper** so **landscape** is not required! (Thanks to Stephen Sangwine for this contribution  
**legalpaper** which I included unchanged and which explains the metric units.)

```

a3paper
a2paper
a1paper
409 \DeclareOption{a4paper}
410   {\setlength\paperheight {297mm}%
411    \setlength\paperwidth  {210mm}}
412 \DeclareOption{letterpaper}
413   {\setlength\paperheight {11in}%
414    \setlength\paperwidth  {8.5in}}
415 \DeclareOption{ledgerpaper}
416   {\setlength\paperheight {11in}%
417    \setlength\paperwidth  {7.33in}}
418 \DeclareOption{legalpaper}
419   {\setlength\paperheight {14in}%
420    \setlength\paperwidth  {8.5in}}
421 \DeclareOption{a3paper}
422   {\setlength\paperheight {420mm}%
423    \setlength\paperwidth  {297mm}}
424 \DeclareOption{a2paper}
425   {\setlength\paperheight {594mm}%
426    \setlength\paperwidth  {420mm}}
427 \DeclareOption{a1paper}
428   {\setlength\paperheight {840mm}%
429    \setlength\paperwidth  {594mm}}
430 \DeclareOption{35mmSlide}
431   {\setlength\paperheight {11in}%
432    \setlength\paperwidth  {7.33in}}
433 \DeclareOption{Screen4to3}
434   {\setlength\paperwidth  {297mm}%
435    \setlength\paperheight  {0.75\paperwidth}}
436 \DeclareOption{Screen16to9}
437   {\setlength\paperwidth  {297mm}%
438    \setlength\paperheight  {0.5625\paperwidth}}
439 \DeclareOption{landscape}
440   {\setlength\@tempdima  {\paperheight}%
441    \setlength\paperheight {\paperwidth}%
442    \setlength\paperwidth  {\@tempdima}%
443    \@landscapetrue}

```

`\@ptsize` As in the standard L<sup>A</sup>T<sub>E</sub>X classes, this macro holds the point size of the normal font. The available options here are 17pt, 20pt, 25pt, 30pt with 20pt being the default. There is also a special option `shortform` which compresses the full large pages into a shorter form. In this form, text is smaller (generally 12pt), new foils do not cause a page break, only a vertical skip. This is useful for making either hard or soft copy for redistribution (to save paper).

```
444 \newcommand\@ptsize{}
445 \DeclareOption{shortform}{\renewcommand\@ptsize{shrt}}
446 \DeclareOption{17pt}{\renewcommand\@ptsize{17}}
447 \DeclareOption{20pt}{\renewcommand\@ptsize{20}}
448 \DeclareOption{25pt}{\renewcommand\@ptsize{25}}
449 \DeclareOption{30pt}{\renewcommand\@ptsize{30}}
```

The next few options are standard L<sup>A</sup>T<sub>E</sub>X: `leqno`, `fleqn`, `draft`, `final`, `openbib`.

```
450 \DeclareOption{leqno}{\input{leqno.clo}}
451 \DeclareOption{fleqn}{\input{fleqn.clo}}
452 \DeclareOption{draft}{\setlength\overfullrule{5pt}}
453 \DeclareOption{final}{\setlength\overfullrule{0pt}}
454 \DeclareOption{openbib}{\@openbibtrue}
```

`headrule` The “rule” options enable rules in the header and footer.

`footrule`

```
455 \DeclareOption{headrule}{\@header@ruletrue}
456 \DeclareOption{footrule}{\@footer@ruletrue}
```

`dvips|dvipsonel|vtex` One of the `dvips`, `dvipsonel` or `vtex` option are *required* for the rotation of individual foils. We also use this together with the `landscape` option to issue the `\special{landscape}` required to rotate the whole document. This just saves the user from doing it.

```
457 \DeclareOption{dvips}{\@dvipstrue}
458 \DeclareOption{dvipsonel}{\@dvipsonetrue}
459 \DeclareOption{vtex}{\@vtextrue}
```

`magscalefonts` These two options control the conditionals which trigger changes in the use of the

`useDCfonts` T1 encoding. See Section ?? for more details.

```
460 \DeclareOption{magscalefonts}{\@magscaleECfontstrue}
461 \DeclareOption{useDCfonts}{\@useDCfontstrue}
```

Because a number of standard L<sup>A</sup>T<sub>E</sub>X options don’t make sense in FoilT<sub>E</sub>X, we have disabled them. These options are `a5paper`, `b5paper`, `executivepaper`, `10pt`, `11pt`, `12pt`, `oneside`, `twoside`, `openright`, `openany`, `titlepage`, `notitlepage`, `onecolumn`, `twocolumn`. With the exceptions of `oneside`, `titlepage`, `onecolumn`, they all return a warning to the user. In the case of point size options, suggestions are given to the user to try the official FoilT<sub>E</sub>X size options. (Note, in versions prior to 2.1.3, `legalpaper` was not available.)

```
462 \DeclareOption{a5paper}{%
463   \ClassWarningNoLine{FoilTeX}{No 'a5paper' option for foils.}}
464 \DeclareOption{b5paper}{%
465   \ClassWarningNoLine{FoilTeX}{No 'b5paper' option for foils.}}
466 \DeclareOption{executivepaper}{%
467   \ClassWarningNoLine{FoilTeX}{No 'executivepaper' option for foils.}}
```

```

468 \DeclareOption{10pt}{%
469   \ClassWarningNoLine{FoilTeX}{No '10pt' foils option, try shortform,
470     17pt, 20pt, 25pt or 30pt (defaulting to 20pt).}}
471 \DeclareOption{11pt}{%
472   \ClassWarningNoLine{FoilTeX}{No '11pt' foils option, try shortform,
473     17pt, 20pt, 25pt or 30pt (defaulting to 20pt).}}
474 \DeclareOption{12pt}{%
475   \ClassWarningNoLine{FoilTeX}{No '12pt' foils option, try shortform,
476     17pt, 20pt, 25pt or 30pt (defaulting to 20pt).}}
477 \DeclareOption{oneside}{}
478 \DeclareOption{twoside}{%
479   \ClassWarningNoLine{FoilTeX}{No 'twoside' option for foils.}}
480 \DeclareOption{openright}{%
481   \ClassWarningNoLine{FoilTeX}{No 'openright' option for foils.}}
482 \DeclareOption{openany}{%
483   \ClassWarningNoLine{FoilTeX}{No 'openany' option for foils.}}
484 \DeclareOption{titlepage}{}
485 \DeclareOption{notitlepage}{%
486   \ClassWarningNoLine{FoilTeX}{No 'notitlepage' option for foils.}}
487 \DeclareOption{onecolumn}{}
488 \DeclareOption{twocolumn}{%
489   \ClassWarningNoLine{FoilTeX}{No 'twocolumn' layout for foils.}}

```

Here we execute the default options and do the processing of the document class option list and what is specified in the `foiltex.cfg` file if one exists. We add to this output to the dvi file of the `\special{landscape}` if the user has the `landscape` *and* one of the `dvips`, `dvipsone` or `vtex` options declared. When `VTeX` is autodetected the `vtex` option is not required and the `dvips` and `dvipsone` options are disabled. Version 2.1.4 adds `PDFLATEX` auto-detection. This code was supplied by Hans Fredrik Nordhaug, which he claims was borrowed from Heiko Oberdiek `ifpdf` package. It also suppressed the other driver options (except the `vtex` as I don't know how this integrates with `VTeX`.)

```

490 \ExecuteOptions{letterpaper,20pt,final}
491 \InputIfFileExists{foiltex.cfg}{}{}
492 \ProcessOptions
493 \ifx\pdfoutput\undefined
494 \else
495   \ifx\pdfoutput\relax
496   \else
497     \ifcase\pdfoutput
498     \else
499       \@pdftrue
500     \fi
501   \fi
502 \fi
503 \if@vtex
504   \if@dvips
505     \ClassWarningNoLine{FoilTeX}{%
506       Option 'dvips' is ignored when running vtex}
507   \fi
508   \if@dvipsone
509     \ClassWarningNoLine{FoilTeX}{%
510       Option 'dvipsone' is ignored when running vtex}
511   \fi

```

```

512 \@dvipsfalse\@dvipsonefalse
513 \fi
514 \if@pdftex
515   \if@dvips
516     \ClassWarningNoLine{FoilTeX}{%
517       Option 'dvips' is ignored when running pdflatex}
518   \fi
519   \if@dvipsone
520     \ClassWarningNoLine{FoilTeX}{%
521       Option 'dvipsone' is ignored when running pdflatex}
522   \fi
523 \@dvipsfalse\@dvipsonefalse
524 \fi
525 \if@landscape
526 % \if@dvips{\special{landscape}}\else%
527 \if@dvipsone{\special{landscape}}%

```

With V<sub>T</sub>E<sub>X</sub>, landscape mode is handled in different ways in PDF and PostScript mode:

- In PDF mode, the MediaSize is determined from the landscape paper size, as usual.
- In PS mode, the BoundingBox is set to the corresponding *portrait* paper size, and the page contents is rotated, so that the foils can easily be printed on portrait-oriented paper.

```

528 \else\if@vtex\ifnum\OpMode=2{%
529   \immediate\special{landscape}%
530   \AtBeginDocument{\mediaheight=\paperwidth\mediawidth=\paperheight}%
531 } \fi
532 \fi\fi
533 % \fi
534 \fi

```

Finally we are ready to load the other Foil<sub>T</sub>E<sub>X</sub> external files required. The first checks to see if there is a `ftlfonts.cfg` file which contains local alternative font definitions. If not, then we load the default font definition information. (This was changed in version 2.1.4 to accommodate systems like V<sub>T</sub>E<sub>X</sub> which might want to customize font usage without modifying the default files.) The default font definitions include font shape data usually stored in `.fd` files; we put them together for simplicity and to reduce the number of files loaded. The second is the file used for the size option.

```

535 \InputIfFileExists{ftlfonts.cfg}{\input{ftlfonts.def}}
536 \input{foil\@ptsize.clo}

```

## 11.2 Some basic macros

`\FoilTeX` Of course, we have to define the Foil<sub>T</sub>E<sub>X</sub> logo. As is done for the L<sub>A</sub>T<sub>E</sub>X logos, We use the new `\DeclareRobustCommand`. Note that, in contrast with the other logos, we force the Foil<sub>T</sub>E<sub>X</sub> logo to always appear in the same font family, shape and series with only the size varying.

```

537 \DeclareRobustCommand\FoilTeX{{\normalfont%
538   {\sffamily Foil}\kern-.03em{\rmfamily\TeX}}}

```

`underscore` The underscore in L<sup>A</sup>T<sub>E</sub>X is too thin, in fact it has fixed thickness independent of the font size. This makes some sense if the font sizes aren't allowed to vary that much. We fix it here so that it varies with font size always.

```
539 \renewcommand\_ {\leavevmode\kern.06em\vbox{\hrule width.4em height.12ex}}
```

`\footnoterule` The default L<sup>A</sup>T<sub>E</sub>X footnote rule is too short (2in) on foils so we make it longer.  
`\@makefnmark` Note that the thickness of the rule is still the same (.4pt). The macro for making the footnote text is not part of the default format but is defined in class files like `article.cls`. We steal that definition and put it here. Curiously, the macro for making the footnote mark *is* defined in the format (`latex.ltx`), but we fix it here so that it gets sans serif numerals.

```
540 \renewcommand\footnoterule{\kern-3\p@\hrule width.4\textwidth\kern2.6\p@}
541 \newcommand\@makefnmark[1]{\parindent 1em\noindent
542 \hbox to 1.8em{\hss\@makefnmark}#1}
543 \def\@makefnmark{\hbox{$^{\mathsf{\@thefnmark}}\m@th$}}
```

`\marginpar` The default definition of `\marginpar` doesn't work well in FoilT<sub>E</sub>X because of the lack of hyphenation, the large size of the fonts and the very narrow space for these items. So, we fix it a little by forcing it to be `\raggedright` (for right margin paragraphs) and `\raggedleft` (for left margin paragraphs). We cheat here so that we don't need to worry about what is happening in L<sup>A</sup>T<sub>E</sub>X's innards in this context.

```
544 \let\@oldmarginpar\marginpar
545 \def\@marginragged{\if@reversemargin\raggedleft\else\raggedright\fi}
546 \def\@foilmarginpar{\ifnextchar[{\@foilmarginparRL}{\@foilmarginparR}}
547 \def\@foilmarginparRL[#1]#2{%
548 \@oldmarginpar[{\@marginragged #1\par}]{\@marginragged #2\par}}
549 \def\@foilmarginparR#1{\@oldmarginpar{\@marginragged #1\par}}
550 \let\marginpar\@foilmarginpar
```

`\Black` Stricly speaking, we probably shouldn't define these and they shouldn't be part of a FoilT<sub>E</sub>X class file, since they are not completely compatible with the color package. However, we still define them and use them for two purposes. First is backward compatibility with old FoilT<sub>E</sub>X documents, and second, so that things still work reasonably well with the old `colordvi` style file. They are both defined as no-ops.

```
551 \def\Black#1{#1}
552 \def\globalColor#1{#1}
```

`\today` Since this one isn't defined by default, we define it.

```
553 \newcommand\today{\ifcase\month\or
554 January\or February\or March\or April\or May\or June\or
555 July\or August\or September\or October\or November\or December\fi
556 \space\number\day, \number\year}
```

`\lineskip` Next, we set a few of the basic space parameters. Note that we have increased the `\parindent` in the new version but retained the old value in compatibility mode for old versions of FoilT<sub>E</sub>X files. The value for baseline stretch is not strictly needed since that is the default. We put it here for completeness. We adjust the spacing set by `\jot` in the new mode, since we found we used this a lot in practice.  
`\jot` We left it as the default in compatibility mode.

```

557 \setlength\lineskip{1\p@}
558 \setlength\normallineskip{1\p@}
559 \renewcommand\baselinestretch{1}
560 \setlength\parskip{18\p@ \@plus 4\p@ \@minus 4\p@}
561 \if@compatibility
562 \setlength\parindent{15\p@}
563 \setlength\jot{3\p@}
564 \else
565 \setlength\parindent{30\p@}
566 \setlength\jot{10\p@}
567 \fi

```

`\righthyphenmin` `\lefthyphenmin` We set these minimum hyphenation values to some large value so that we can disable hyphenation. This is unlike `FoilTEX v1.0.1`, where we turned off hyphenation by disabling the hyphenation tables. This is more or less essential here since the tables are already loaded by the `LATEX` format. It does have the additional advantage in that the user can re-enable it simply by resetting these values.

```

568 \righthyphenmin=100
569 \lefthyphenmin=100

```

`\@eqnnum` `\theequation` We set the equation number in the default sans serif font (don't exactly know why this is necessary — maybe it is not!) and place it in arabic numerals.

```

570 \def\@eqnnum{\hbox{\reset@font\sffamily (\theequation)}}
571 \renewcommand\theequation{\arabic{equation}}

```

`titlepage` `\@pnumwidth` `\@tocrmarg` `\@dotsep` We leave the next set of macros here, even though they are either irrelevant or taken care of by other things (like `\maketitle`), just in case someone wants to use them. They are not supported except in compatibility mode. The parameter settings are used only in the table of contents (which we don't have on foils), so these are irrelevant.

```

572 \if@compatibility
573 \newenvironment{titlepage}{%
574 \@restonecolfalse \newpage \thispagestyle{empty}
575 \setcounter{page}{0}}{\newpage}
576 \newcommand\@pnumwidth{1.55em}
577 \newcommand\@tocrmarg {2.55em}
578 \newcommand\@dotsep{4.5}
579 \fi

```

`\sloppyfoils` We can be really sloppy with tolerances and fuzz on foils, so we set the parameters for this and invoke (probably could just avoid the definition all together).

```

580 \def\sloppyfoils{\tolerance 9000 \hfuzz 2\p@ \vfuzz 2\p@ \hbadness 2000}
581 \sloppyfoils

```

### 11.3 List environments: spacing

In this subsection, we set up all the code needed for list environments spacing. Most of this is extracted in some form or another from the basic `LATEX` classes like `article` with some modifications for use in foils.

`\leftmargin*` We begin with the list margin indentation parameters.



$\geq 20\text{pt}$	<code>\@listIa</code>
17pt	<code>\@listIb</code>
14pt	<code>\@listIc</code>
12pt, shortform	<code>\@listId</code>

Table 5: Usage of `\@listI*` styles versus font size in L<sup>A</sup>T<sub>E</sub>X<sub>2</sub>e mode.

```

582 \setlength\leftmargini{25\p@}
583 \setlength\leftmarginii{22\p@}
584 \setlength\leftmarginiii{18.7\p@}
585 \setlength\leftmarginiv{17\p@}
586 \setlength\leftmarginv{10\p@}
587 \setlength\leftmarginvi{10\p@}
588 \setlength\leftmargin\leftmargini

```

`\labelwidth` We need to set the label width and label separation parameters. Unfortunately,  
`\labelsep` they were done in the wrong order in the old Foil<sub>T</sub>E<sub>X</sub>, so here we do it right but  
under compatibility mode, do it the old way so things don't change.

```

589 \if@compatibility
590 \setlength\labelwidth\leftmargini\advance\labelwidth-\labelsep
591 \setlength\labelsep{.5em}
592 \else
593 \setlength\labelsep{10\p@}
594 \setlength\labelwidth\leftmargini\advance\labelwidth-\labelsep
595 \fi

```

`\partopsep` This is set fairly small, no reason to be too spacious.

```

596 \setlength\partopsep{2\p@ \@plus 1\p@ \@minus 1\p@}

```

`\@listIa` These macros define the spacing for top level list environments. We define four  
`\@listIb` default sets of parameters and overlap their usage in the various point size class  
`\@listIc` option files. Table ?? shows the usage of each with respect to font size. (This  
`\@listId` table is somewhat different in compatibility mode, particularly for small relative  
font sizes in the larger class options. See Section ?? for the details.)

```

597 \newcommand\@listIa{\leftmargin\leftmargini
598 \topsep 14\p@ \@plus 2\p@ \@minus 4\p@
599 \parsep 14\p@ \@plus 4\p@ \@minus 4\p@
600 \itemsep 14\p@ \@plus 4\p@ \@minus 2\p@}
601 \newcommand\@listIb{\leftmargin\leftmargini
602 \topsep 8\p@ \@plus 2\p@ \@minus 2\p@
603 \parsep 2\p@ \@plus 1\p@ \@minus 1\p@
604 \itemsep \parsep}
605 \newcommand\@listIc{\leftmargin\leftmargini
606 \topsep 6\p@ \@plus 1\p@ \@minus 1\p@
607 \parsep 2\p@ \@plus 1\p@ \@minus 1\p@
608 \itemsep \parsep}
609 \newcommand\@listId{\leftmargin\leftmargini
610 \topsep 4\p@ \@plus 1\p@ \@minus 1\p@
611 \parsep 2\p@ \@plus 1\p@ \@minus 1\p@
612 \itemsep \parsep}

```

`\@listi*` Now we set the parameters for lower level lists. These are fixed throughout all the point sizes. Essentially, there is very little additional space here except the indentation. We allowed a fair amount of space in the top level, however. We close this section with a call to `\normalsize` to make sure that all the internal list macros are defined appropriately. This call is also done in each of the `foil*.clo` files but before the above parameters sets are defined. This caused a problem by delaying the definition of `\@listi`. This is new in version 2.1.1. (Alternatively, we could move all this stuff *before* we load these `.clo` files but that seemed to be too much of a change.)

```

613 \newcommand\@listiif{\leftmargin\leftmarginii
614 \labelwidth\leftmarginii\advance\labelwidth-\labelsep
615 \topsep \z@
616 \parsep \z@
617 \itemsep \parsep}
618 \newcommand\@listiii{\leftmargin\leftmarginiii
619 \labelwidth\leftmarginiii\advance\labelwidth-\labelsep
620 \partopsep 1\p@ \@plus 0\p@ \@minus 1\p@
621 \topsep \z@
622 \parsep \z@
623 \itemsep \topsep}
624 \newcommand\@listiv{\leftmargin\leftmarginiv
625 \labelwidth\leftmarginiv\advance\labelwidth-\labelsep}
626 \newcommand\@listv{\leftmargin\leftmarginv
627 \labelwidth\leftmarginv\advance\labelwidth-\labelsep}
628 \newcommand\@listvi{\leftmargin\leftmarginvi
629 \labelwidth\leftmarginvi\advance\labelwidth-\labelsep}
630 \normalsize

```

`\zerolistvertdimens` We define this macro in the new version so we have a simple mechanism for shrinking as much as possible all the vertical space in list environments.

```

631 \if@compatibility
632 \let\zerolistvertdimens\relax
633 \else
634 \def\zerolistvertdimens{\parskip0pt\topsep0pt\partopsep0pt%
635 \parsep0pt\itemsep0pt}
636 \fi

```

## 11.4 List environments: structure

Here we take up the structure of list environments including the standard environments like `verse` and `description`

`\@item` We start by redefining `\@item` in compatibility mode to get the effect we had before for protecting the item label from spurious color corruption. This of course will only work with the `colordvi` style. As mentioned above, this is not the recommended way to do color in the new  $\text{\LaTeX}$ . This code is mostly taken from the new  $\text{\LaTeX}$  and modified to fit the old needs. The only real change is in the addition of the `\globalColor` macro surrounding the `\makelabel`.

```

637 \if@compatibility
638 \def\@item[#1]{%
639 \if@nparitem

```

```

640     \@donoparitem
641   \else
642     \if@inlabel \indent \par \fi
643     \ifhmode \unskip\unskip \par \fi
644     \if@newlist
645       \if@nobreak
646         \@nbitem
647       \else
648         \addpenalty\@beginparpenalty
649         \addvspace\@topsep \addvspace{-\parskip}
650       \fi
651     \else
652       \addpenalty\@itempenalty \addvspace\itemsep
653     \fi
654     \global\@inlabeltrue
655   \fi
656 \everypar{\global\@minipagefalse\global\@newlistfalse
657   \if@inlabel
658     \global\@inlabelfalse \hskip -\parindent \box\@labels \penalty\z@
659   \fi
660   \everypar{}}
661 \global\@nobreakfalse
662 \if@noitemarg \@noitemargfalse
663 \if@nmbrrlist \refstepcounter{\@listctr}\fi
664 \fi
665 \sbox\@tempboxa{\globalColor{\makeLabel{#1}}} \global\setbox\@labels
666 \hbox{\unhbox\@labels \hskip \itemindent
667   \hskip -\labelwidth \hskip -\labelsep
668   \ifdim
669     \wd\@tempboxa >\labelwidth \box\@tempboxa
670   \else
671     \hbox to\labelwidth {\unhbox\@tempboxa}
672   \fi
673   \hskip \labelsep}
674 \ignorespaces
675 }
676 \fi

```

`\theenum*` We set up the default format for the enumeration list numbers at the four default levels. Similarly, we default the tags for the itemized lists.

```

\labelenum*
\labelitem*
677 \renewcommand\theenumi{\arabic{enumi}}
678 \renewcommand\theenumii{\alph{enumii}}
679 \renewcommand\theenumiii{\roman{enumiii}}
680 \renewcommand\theenumiv{\Alph{enumiv}}
681 \renewcommand\p@enumii{\theenumi}
682 \renewcommand\p@enumiii{\theenumi(\theenumii)}
683 \renewcommand\p@enumiv{\p@enumiii\theenumiii}
684 \newcommand\labelenumi{\theenumi.}
685 \newcommand\labelenumii{\theenumii)}
686 \newcommand\labelenumiii{\theenumiii.}
687 \newcommand\labelenumiv{\theenumiv.}
688 \newcommand\labelitemi{\m@th\bullet$}
689 \newcommand\labelitemii{\normalfont\bfseries --}}
690 \newcommand\labelitemiii{\m@th\ast$}

```

```

691 \newcommand\labelitemiv{\m@th\cdot$}

\descriptionlabel Finally, we predefine the standard environments which are built from the list
description environment.
    verse
quotation 692 \newcommand\descriptionlabel[1]{\hspace\labelsep \normalfont\bfseries #1}
quote      693 \newenvironment{description}{\list{}{\labelwidth\z@
694 \itemindent-\leftmargin \let\makelabel\descriptionlabel}}{\endlist}
695 \newenvironment{verse}{\let\=\@centercr
696 \list{}{\itemsep\z@ \itemindent -1.5em\listparindent \itemindent
697 \rightmargin\leftmargin\advance\leftmargin 1.5em}\item[]}{\endlist}
698 \newenvironment{quotation}{\list{}{\listparindent 1.5em
699 \itemindent\listparindent
700 \rightmargin\leftmargin \parsep 0\p@ \@plus 1\p@}\item[]}{\endlist}
701 \newenvironment{quote}{\list{}{\rightmargin\leftmargin}\item[]}{\endlist}

```

## 11.5 Page layout parameters

In this section we setup the parameters that adjust the page layout, including margins, text height and width, etc.

```

\oddsidemargin We start with the margin settings and the header settings. Some things change
\evensidemargin a little in the new version so we keep the old versions in compatibility mode.
\topmargin This is mostly for the footer stuff. Of course, the \footheight, @maxsep and
\headsep @dblmaxsep are no-ops in all cases but is only defined in compatibility mode.
\headheight In the default mode (i.e., non-compatibility) the \head@footskip length contains
\footskip the sum of the vertical space taken by the header and footer. The description of
\head@footskip this is given below. Initially it is set to one inch and the \footskip is calculated
\footnotesep from this.
\footins
\mpfootins 702 \setlength\oddsidemargin{0\p@}
703 \setlength\evensidemargin{0\p@}
704 \setlength\topmargin{0\p@}
705 \setlength\headsep{14\p@}
706 \setlength\headheight{15\p@}
707 \ifcompatibility
708 \setlength\footheight{25\p@}
709 \setlength\footskip{45\p@}
710 \setlength\@maxsep{20\p@}
711 \setlength\@dblmaxsep{20\p@}
712 \else
713 \newdimen\head@footskip
714 \setlength\head@footskip{1in}
715 \setlength\footskip{\head@footskip}
716 \addtolength\footskip{-\headsep}
717 \addtolength\footskip{-\headheight}
718 \fi
719 \setlength\footnotesep{10\p@}
720 \setlength{\skip\footins}{9\p@ \@plus 4\p@ \@minus 2\p@}
721 \skip\mpfootins = \skip\footins

\marginparwidth Here we set up the dimensions for margin paragraphs. We base these on one inch
\marginparsep margins, so if the user choses to shrink these margins and plans to use margin
\marginparpush paragraphs, they should be careful about these dimensions.

```

```

722 \setlength\marginparwidth{54\p@}
723 \setlength\marginparsep{10\p@}
724 \setlength\marginparpush{5\p@}

```

`\textheight` We have added in the new version a `\@foilheight` and `\@foilwidth` which are  
`\textwidth` internal dimensions of the printable area of the page (excluding margin paragraphs  
`\@foilheight` and the like). They are setup initially as the paper dimensions less two inches  
`\@foilwidth` (each) since we set the default top margin and side margins to zero. This leaves  
`\@rottdimens` exactly a one inch margin all the way around in all supported paper sizes. At  
`\@defaultdimens` the `\begin{document}` we invoke a macro (`\setp@gelayoutdimens`) that adjusts  
`\@rottdimens@pdf` these dimensions to account for user settings for page layout. Furthermore, it  
`\@defaultdimens@pdf` defines the internal commands `\@rottdimens` and `\@defaultdimens` which are used  
`\setp@gelayoutdimens` to perform the rotation of individual pages (including header and footer). Set up  
this way, the macros can take into account the rotation of the whole document done  
by a `landscape` class option (since this is based only on the paper dimensions).

In compatibility mode, we use the parameter settings of FoilTeX v1.0.1 for text height but in the new version we let the text height expand to its largest possible subject to space for header and margins. Also in this mode, we disable the `\@rottdimens` and `\@defaultdimens` since we didn't support this in the old version.

Note: I understand the `dvips` can set the paper sizes automatically with a `\special` command. However, I've chosen not to use that here because (a) limitations in my testing environment and (b) possible incompatibilities with other drivers.

We've included some additional code to deal with another incompatibility with `hyperref`. This again is provided by Heiko Oberdiek via Hans Fredrik Nordhaug.

Finally, version 2.1.4 provides additional page dimension manipulations for PDFLaTeX. This was provided by in a number of similar forms by a few people. See Section ??.

```

725 \if@compatibility
726 \setlength\textheight{7.6in}
727 \setlength\textwidth{6.5in}
728 \let\@rottdimens\relax
729 \let\@defaultdimens\relax
730 \else
731 \newdimen\@foilheight
732 \newdimen\@foilwidth
733 \setlength\textheight{\paperheight}
734 \addtolength\textheight{-2in}
735 \addtolength\textheight{-\head@footskip}
736 \setlength\textwidth{\paperwidth}
737 \addtolength\textwidth{-2in}
738 \def\setp@gelayoutdimens{%
739 \setlength\head@footskip{\footskip}
740 \addtolength\head@footskip{\headsep}
741 \addtolength\head@footskip{\headheight}
742 \setlength\@foilheight{\textheight}
743 \addtolength\@foilheight{\head@footskip}
744 \setlength\@foilwidth{\textwidth}
745 \def\@rottdimens{\textheight\@foilwidth \textwidth\@foilheight
746 \addtolength\textheight{-\head@footskip}

```

```

747     \vsize\textheight \hsize\textwidth \linewidth\textwidth
748     \columnwidth\textwidth \@colroom\textheight \@colht\textheight}
749 \def\@rottdimens@pdf{%
750     \setlength{\pdfpagewidth}{\strip@pt\paperheight truept}%
751     \setlength{\pdfpageheight}{\strip@pt\paperwidth truept}}
752 \def\@defaultdims{\textheight\@foilheight \textwidth\@foilwidth
753     \addtolength\textheight{-\head@footskip}
754     \vsize\textheight \hsize\textwidth \linewidth\textwidth
755     \columnwidth\textwidth \@colroom\textheight \@colht\textheight}
756 \def\@defaultdims@pdf{%
757     \setlength{\pdfpagewidth}{\strip@pt\paperwidth truept}%
758     \setlength{\pdfpageheight}{\strip@pt\paperheight truept}}
759 \@defaultdims
760 \if@pdftex\@defaultdims@pdf\fi % end of \def\setp@gelayoutdims
761 \fi
762 \AtBeginDocument{\if@compatibility\else\setp@gelayoutdims\fi
763 % For \texttt{dvips} we use the \texttt{papersize} special
764 % so user's don't have to invoke \texttt{dvips} with the
765 % \texttt{-t papersize} option. This may also be usable with
766 % \texttt{dvipsone} but we have no way to test that. (Thanks to
767 % Hans Fredrik Nordhaug for this fix.)
768 \if@dvips
769     \AtBeginDvi{\special{%
770         papersize=\the\paperwidth,\the\paperheight}}%
771     \fi
772     \ifpackageloaded{hyperref}{%
773 \def\@begindvi{\foil@begindvi \unvbox \@begindvibox
774         \ifHy@pageanchor \@hyperfixhead
775         \gdef\@begindvi{\foil@begindvi\@hyperfixhead}%
776     \else
777         \gdef\@begindvi{\foil@begindvi\HyPL@EveryPage}%
778     \fi}}}%
779 }

```

**\@\*penalty** A number of parameters for float separation and the like are set to the defaults in L<sup>A</sup>T<sub>E</sub>X (both old and new versions) so we leave out settings for these in this class file. We do set up the penalty values (not really knowing what they do) to values consistent with other class files and old style files.

```

780 \@lowpenalty 51
781 \@medpenalty 151
782 \@highpenalty 301
783 \@beginparpenalty -\@lowpenalty
784 \@endparpenalty -\@lowpenalty
785 \@itempenalty -\@lowpenalty

```

**\arraycolsep** Here are some settings for space in tables and tabbing environments. These aren't terribly critical but something has to be set.

```

\arraycolsep
\arrayrulewidth
\doublerulesep
\tabbingsep
786 \setlength\arraycolsep{10\p@}
787 \setlength\tabcolsep{12\p@}
788 \setlength\arrayrulewidth{1\p@}
789 \setlength\doublerulesep{3\p@}
790 \setlength\tabbingsep\labelsep

```

`\fboxsep` And finally some settings for the frame box rule and separation. We make the  
`\fboxrule` separation a bit bigger to compensate for the larger fonts.

```
791 \if@compatibility
792 \setlength\fboxsep{6\p@}
793 \else
794 \setlength\fboxsep{10\p@}
795 \fi
796 \setlength\fboxrule{1\p@}
```

## 11.6 The title page

In this section we describe the construction of the title page macros.

`\abovetitleskip` I'm a big fan of letting the user easily adjust spacing in lots of different contexts,  
`\titleauthorskip` so we set all the vertical spacing parameters as adjustable lengths instead of hard-  
`\authorauthorskip` coding their values. This may take too many  $\TeX$  resources but hopefully not  
`\authordateskip` (I'm sure I'll get messages about this if it does). Each of these dimensions adjust  
`\dateabstractskip` vertical space on the title page. Each name indicates where the space is, so the  
user can easily shrink or stretch space as necessary. The default values are as in  
the old  $\text{Foil}\TeX$  v1.0.1, so this should cause no additional confusion.

```
797 \newlength\abovetitleskip
798 \newlength\titleauthorskip
799 \newlength\authorauthorskip
800 \newlength\authordateskip
801 \newlength\dateabstractskip
802 \setlength\abovetitleskip{2em}
803 \setlength\titleauthorskip{1.5em}
804 \setlength\authorauthorskip{.5em}
805 \setlength\authordateskip{1em}
806 \setlength\dateabstractskip{1em}
```

`\maketitle` We don't do too much that is not in `article.cls` for defining the `\maketitle`  
`\@maketitle` and `\@maketitle` commands. About the only differences are the addition of these  
adjustable spacing parameters. (By changing the way footnote marks are done  
overall, we no longer need to change the definitions within the `\maketitle` as in  
the old  $\text{Foil}\TeX$ .) This fixed a bug when the user tried to redefine the footnote  
mark in terms of the footnote symbols.

```
807 \def\maketitle{\par
808 \begingroup
809 \setcounter{page}{0}
810 \def\thefootnote{\fnsymbol{footnote}} \newpage
811 \@maketitle
812 \thispagestyle{foilheadings}
813 \@thanks
814 \endgroup
815 \setcounter{footnote}{0}
816 \let\maketitle\relax \let\@maketitle\relax
817 \gdef\@thanks{ }\gdef\@author{ }\gdef\@title{ }\let\thanks\relax%
818 }
```

Note that in `\@maketitle` we use the `\zerolistvertdimens` to get all the list spacing shrunk to zero so we can control it explicitly with the above parameters.

```

819 \def\@maketitle{\newpage
820   \zerolistvertdimens
821   \if@compatibility\else
822     \advance\abovetitleskip -\baselineskip % \null adds this space
823   \fi
824   \null\vskip\abovetitleskip
825   \begin{center}
826     {\Large\bfseries \@title \par}
827     \vskip\titleskip
828     {\lineskip \authorauthorskip
829       \begin{tabular}[t]{c}\@author\end{tabular}
830       \par}
831     \vskip\authordateskip {\@date}
832   \end{center}
833   \par\vfil
834 }
```

`\abstractname` To complete the title page, we add the code for the abstract environment, if desired  
`abstract` by the user. We define the `\abstractname` so the user can do this in their favorite language. We then construct the environment using the new parameters and still try to simulate the old layout.

```

835 \newcommand\abstractname{Abstract}
836 \newenvironment{abstract}{%
837   \if@compatibility
838     \dateabstractskip\parskip
839     \advance\dateabstractskip\topsep
840     \advance\dateabstractskip\baselineskip
841   \fi
842   \vskip\dateabstractskip
843   \centerline{\reset@font\bfseries\abstractname}
844   \if@compatibility\vspace{-.5em}\vspace{0\p@}\fi
845   \list{}{\listparindent 1.5em
846     \itemindent\listparindent \rightmargin\leftmargin
847     \zerolistvertdimens
848     }\item[]%
849   }{\endlist\vfill}
```

## 11.7 Page style

We have now arrived at the part of the code that deals with the page style, headers, footers, etc.

`\leftheader` We start with three corners of the page (all but the bottom left corner). These  
`\righthead` are simply controlled using the next set of declaration macros. They each define  
`\rightfoot` internal macros which are placed in the appropriate place in the header and footer.  
`\@lefthead` The default definitions for the header is empty and for the right footer is the page  
`\@righthead` number.  
`\@rightfoot`

```

850 \newcommand\leftheader[1]{\gdef\@leftheader{#1}}
851 \newcommand\righthead[1]{\gdef\@righthead{#1}}
852 \newcommand\rightfoot[1]{\gdef\@rightfoot{#1}}
```



```

853 \lefthead{}
854 \righthead{}
855 \rightfoot{\quad\textsf{\thepage}}

```

**\ifLogo** The left footer is a combination of two macros, **\MyLogo** and **\Restriction**. By default, the logo appears and is set to be the string “Typeset by FoilTEX”. The **\LogoOff** **\LogoOn** **\Restriction** is empty, but can be used for things like “Confidential” or perhaps for something that is aimed to the intended audience. The **\LogoOff** and **\LogoOn** declarations are conditional toggles that turn on or off the setting of the logo. The conditional they set is tested by **\ifLogo**, which defaults to true. This gives a simple mechanism for turning it off completely, or perhaps on individual pages as necessary.

```

856 \newif\ifLogo \Logotrue
857 \newcommand\LogoOff{\Logofalse}
858 \newcommand\LogoOn{\Logotrue}
859 \newcommand\Restriction[1]{\gdef\@Restriction{#1}}
860 \Restriction{}
861 \newcommand\MyLogo[1]{\gdef\@MyLogo{\ifLogo{#1}\else\fi}}
862 \MyLogo{-- Typeset by \FoilTeX --}

```

**\ps@foilheadings** Now that we have the code so the user can easily set up the contents of the page style, we need to use these to construct the page style. We have added some extras to this new version. In particular, we now support a rule below the header and a rule above the footer (much as is available with **fancyheadings.sty**). We still wrap everything in the **\Black** macro for backwards compatibility and just in case the user decides to use **colordvi.sty**, though we don’t recommend it or really support it. Note that these headings are different on the title page. We also clean this up abit from the old version by using **\let** to do the even pages.

We made changes here to fix a problem with the footrule being placed over a graphic in the footer if the graphic was too tall.

```

863 \newsavebox\@tempfootbox
864 \newdimen\@tempfootht
865 \newcommand\ps@foilheadings{\let\@mkboth\@gobbletwo
866   \def\@oddhead{%
867     \ifnum \c@page>0
868       {\Black%
869         \if@header@rule\hbox to\z@{\rule[-5\p@]{\textwidth}{1\p@}\hss}\fi
870         \reset@font\tiny
871         \@lefthead\hfil\@righthead}}%
872     \else
873       \hfill
874     \fi}%
875   \def\@oddfoot{%
876     \ifnum \c@page>0
877       {\Black%
878         \sbox\@tempfootbox{\tiny\@MyLogo\ \@Restriction\hfil\@rightfoot}%
879         \@tempfootht\ht\@tempfootbox
880         \advance\@tempfootht 5.66666\p@
881         \if@footer@rule%
882         \hbox to\z@{\rule[\@tempfootht]{\textwidth}{1\p@}\hss}%
883         \fi%

```

```

884     \reset@font\tiny
885     \@MyLogo\ \@Restriction\hfil\@rightfooter}}%
886     \else
887         {\Black{\hfil\reset@font\footnotesize%
888             \@MyLogo\ \@Restriction\hfil}}%
889         \fi}%
890     \let\@evenhead\@oddhead%
891     \let\@evenfoot\@oddfoot%
892 }
893 \ps@foilheadings

```

`\pagenumbering` Finally, we set the page numbering style, force this to one column (who'd want two column foils anyway) and fill the `\mark` with empty stuff just to cover our bases (this is irrelevant on foils).

```

894 \pagenumbering{arabic}
895 \onecolumn
896 \mark{{}{}}

```

## 11.8 Bibliography or References

`\refname` Though they may not be used very much, we do support a bibliography environment. This is a modified version of that from `article.cls`. The essential changes are the deletion of anything that adjusts the header (e.g., `\mkboth`) since this is irrelevant for foils and the replacement of a sectioning macro with just the placement of the `\refname`, which is defined first.

```

897 \newcommand\refname{References}
898 \newdimen\bibindent
899 \setlength\bibindent{1.5em}
900 \newcommand\newblock{}
901 \newenvironment{thebibliography}[1]{
902     \vskip 3.5ex \@plus -1ex \@minus -.2ex
903     \noindent{\large\bfseries\refname}
904     \vskip 2.3ex \@plus .2ex
905     \list{\@biblabel{\arabic{enumiv}}}%
906     {\settowidth\labelwidth{\@biblabel{#1}}%
907     \leftmargin\labelwidth
908     \advance\leftmargin\labelsep
909     \if@openbib
910         \advance\leftmargin\bibindent
911         \itemindent -\bibindent
912         \listparindent \itemindent
913         \parsep \z@
914     \fi
915     \usecounter{enumiv}%
916     \let\p@enumiv\empty
917     \renewcommand\theenumiv{\arabic{enumiv}}}
918     \if@openbib
919         \renewcommand\newblock{\par}
920     \else
921         \renewcommand\newblock{\hskip .11em \@plus .33em \@minus -.07em}
922     \fi
923     \sloppy\clubpenalty4000\widowpenalty4000%

```

```

924 \sffcode‘\.=\@m\relax}%
925 {\def\@noitemerr{\@latex@warning{Empty ‘thebibliography’ environment}}}%
926 \endlist}

```

## 11.9 Non-floating floats

In this section we construct new definitions for float-type environments that don’t actually float! They will look to the user like any other float environment but will act as if given the [H] (put it HERE!) placement.

```

\abovecaptionskip First we set up some parameters that control the spacing around and within floats.
\belowcaptionskip They have obvious meanings based on their names. The default values for these
\abovefloatskip spaces are as in standard LATEX where most of them are hardcoded. Here we let
\captionfraction the user set them.

```

Many users want the caption to have different width than the text width, so here it can be set by the user. The old Foil<sub>T</sub>E<sub>X</sub> method was to set the dimension `\captionwidth`. This actually introduced a bug when combined with `\rotatefoilhead`. In this new version of Foil<sub>T</sub>E<sub>X</sub>, we do two things. First, we fix the bug, but we also introduce an alternative (and preferred) method for adjusting the caption width with `\captionfraction`. As with other L<sup>A</sup>T<sub>E</sub>X fractions (for floats), this is reset with the `\renewcommand`. The default value is 1.0.

```

927 \newlength\abovecaptionskip
928 \newlength\belowcaptionskip
929 \newlength\@captionwidth
930 \newlength\captionwidth
931 \newcommand\captionfraction{1.0}
932 \newlength\abovefloatskip
933 \setlength\abovecaptionskip{15\p@ \@plus 5\p@ \@minus 5\p@}
934 \setlength\belowcaptionskip{0\p@}
935 \setlength\captionwidth\z@
936 \setlength\abovefloatskip{20\p@ \@plus 5\p@ \@minus 10\p@}

```

```

\ext@table These two are defined only to fill an incompatibility between the hyperref package
\ext@table (which shouldn’t need it as of version 6.66j of that package), but we include it here
just in case it might be needed for some other package (pdflatex?).

```

```

937 \providecommand*\ext@table{lot}%
938 \providecommand*\ext@figure{lof}%

```

```

\@makecaption For non-floating environments like “figure” and “table”, we are going to provide a
\@caption *-form which is unnumbered. To enable that in an easy way, we make a conditional
\caption which can be used to determine whether we are to include counter or not in the
caption. This requires some modifications to a couple of macros. Other changes
are noted below. We modify the standard definition for \@makecaption so that it
uses the \captionwidth parameter (old method) or the \captionfraction (new
method). Then we modify the \@caption macro, removing all the extraneous
stuff that added things to the table of contents and the like. Any text in the
optional argument to a \caption command is just swallowed. Finally we modify
the definition of \caption to skip incrementing a counter in starmode (since there
isn’t one!).

```

```

939 \newif\if@starmode\@starmodefalse
940 \newcommand\@makecaption[2]{%

```

To set the internal `\@captionwidth` we first check for the old method. If `\captionwidth` was set by the user, then we take the minimum of this value and `\hsize`. If not, then the new method sets the caption width by taking the fraction of the `\hsize` in all cases.

```

941 \ifdim\captionwidth>\z@
942   \ifdim\captionwidth>\hsize
943     \setlength\@captionwidth\hsize
944   \else
945     \setlength\@captionwidth\captionwidth
946   \fi
947 \else
948   \setlength\@captionwidth{\captionfraction\hsize}
949 \fi

```

Now we layout the caption itself in something no bigger than the above dimension, but ignoring the counter in `*-mode`.

```

950 \vskip \abovecaptionskip
951 \if@starmode\sbox\@tempboxa{#2}\else\sbox\@tempboxa{#1: #2}\fi%
952 \ifdim \wd\@tempboxa >\@captionwidth
953   \centering\parbox[t]{\@captionwidth}{\unhbox\@tempboxa\par}
954 \else
955   \hbox to\hsize{\hfil\box\@tempboxa\hfil}
956 \fi
957 \vskip\belowcaptionskip}
958 \long\def\@caption#1[#2]#3{\par \begingroup \@parboxrestore \normalsize
959 \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par
960 \endgroup}
961 \def\caption{\if@starmode\else\refstepcounter\@capttype\fi%
962 \@dblarg{\@caption\@capttype}}

```

`\@xfloat` To construct non-floating floats, we need to do a couple of things. First, we take out anything from the `\@xfloat` that refers to placement, since these don't move. We also take out all the float penalty code and anything that saves this stuff in the float list since that is now irrelevant. This cleans up this code considerably. Basically, all it does now is build a box with the appropriate grouping and wrapping. Note that this starts a couple of groups which have to be closed later (at the end of the environment).

```

963 \def\@xfloat#1[#2]{%
964   \def \@capttype {#1}%
965   \ifhmode \@bsphack \fi \vskip\abovefloatskip
966   \vbox\bgroup \color@beginngroup \normalcolor
967   \hsize\columnwidth \@parboxrestore
968   \if@nobreak
969     \def\outer@nobreak{\global\@nobreaktrue}\global\@nobreakfalse
970   \fi}

```

`\end@nonfloat` This macro is used to close the non-float environments. We could have modified the `\end@float` and used that but it seemed like this was simpler.

```

971 \def\end@nonfloat{\par\vskip\z@skip

```

```

972 \color@endgroup
973 \outer@nobreak
974 \egroup}

```

`\newnonfloat` This new macro is a general mechanism for defining or creating non-floating environments. It is probably similar to what can be found in `float.sty`, but we didn't check that for our purposes. Each invocation of this macro will create *two* environments, a non-starred version and a starred version. The starred version is not numbered (and so non-reference-able). The first thing this macro does is define the *name* of the environment, i.e., the non-float type used in the caption. It next defines a counter for the non-starred version of the environment. It sets the style of the counter to arabic (this can probably be overridden by the user, but we haven't tested this). Next it sets the style for the caption structure just as in standard L<sup>A</sup>T<sub>E</sub>X. Finally, it defines the actual environments in terms of `\@float` and `\end@nonfloat`. The former is defined within L<sup>A</sup>T<sub>E</sub>X in terms of `\@xfloat` (modified above).

```

975 \newcommand\newnonfloat[2]{%
976 \expandafter\newcommand\csname#1name\endcsname{#2}%
977 \expandafter\newcounter{#1}%
978 \expandafter\renewcommand\csname the#1\endcsname
979     {\@arabic\csname c#1\endcsname}%
980 \expandafter\newcommand\csname fnum#1\endcsname
981     {\csname#1name\endcsname~\csname the#1\endcsname}%
982 \expandafter\newenvironment{#1}{\@float{#1}}{\end@nonfloat}%
983 \expandafter\newenvironment{#1*}{\@float{#1}\@starmodetrue}%
984     {\end@nonfloat}%
985 }

```

`table` Finally, we use the above constructor to give definitions for the standard `table`,  
`figure` `table*`, `figure`, and `figure*` environments. Note that the starred forms mean  
`\figurename` unnumbered versions and *not* two column versions. The `\newnonfloat` automat-  
`\tablename` ically defines a “name” macro for the non-float. So, for example, the following  
declarations define `\tablename` and `\figurename` to “Table” and “Figure”, re-  
spectively.

```

986 \newnonfloat{table}{Table}
987 \newnonfloat{figure}{Figure}

```

## 11.10 The foil title macros and foil rotation

We next describe the macros for starting new foils. There are some enhancements to the old version here. In particular, we now have a simple way to support rotated foils.

`\foilheadskip` Of course, we have a length parameter that we use to set the vertical spacing around the foil title (called `\foilhead`, perhaps in error). This is set to a new value in the new Foil<sup>T</sup>E<sub>X</sub>, with much more shrinkability. We hope this reduces the amount of manual fiddling usually needed to squeeze that extra bit of stuff on a single foil. The default space between the foil title and the text below it is set as `\parskip+\baselineskip+\foilheadskip+[option]` where the `[option]` comes from the optional argument in the `\foilhead` macro.

```

988 \newlength\foilheadskip
989 \ifcompatibility
990   \setlength\foilheadskip{.25in}
991 \else
992   \setlength\foilheadskip{18\p@ \@plus 0\p@ \@minus 18\p@}
993 \fi

```

`\foil@rot@start` This macro is used exclusively for individual foil rotation and is only called if one of the `dvips`, `dvipsone` or `vtex` options is in place. In effect, this issues a POSTSCRIPT call to translate vertically by the current `\@foilheight` (or in the case of `VTEX` horizontally by `\@foilwidth`) and then do the necessary rotation. We don't need to do any graphics save or restore in this process since it is only invoked at the very beginning of a page where this has just happened. This is disables (mostly) for `PDFLATEX`.

```

994 \ifdvips
995 \def\foil@rot@start{\special{ps:
996   0 \strip@pt\@foilheight\space 72.27 div Resolution mul translate
997   90 neg rotate}}%
998 \else\ifdvipsone
999 \def\foil@rot@start{\special{ps:
1000  0 \strip@pt\@foilheight\space 72.27 mul 65536 mul rmoveto
1001  90 rotate}}%
1002 \else\ifvtex
1003 \def\foil@rot@start{\special{pS:
1004   \strip@pt\@foilwidth\space 72.27 div 72 mul 0 translate
1005   90 neg rotate}}%
1006 \else\ifpdftex
1007 \def\foil@rot@start{}%
1008 \fi\fi\fi\fi

```

`\ifcur@rot@state` We need some mechanism to test the current state of rotation so we know whether  
`\ifnew@rot@state` we should issue the rotation call again if there are two invocations of rotated foils  
in a row. We capture this in these conditionals.

```

1009 \newif\ifcur@rot@state
1010 \newif\ifnew@rot@state

```

`\foilhead` We can now define the macros used for starting new foils, both in standard orienta-  
`\rotatefoilhead` tion and rotated. (Note that standard is not by default portrait if the `landscape`  
class option is set.) These are both defined in terms of `\@foilhead` which is used  
to parse the optional argument for vertical space adjustment. `\foilhead` sets  
the state of the “new” foil to non-rotated, then happily goes off to `\@foilhead`.  
`\rotatefoilhead` is not supported in compatibility mode so it isn't even defined  
there. Rotation is not supported unless one of the `dvips`, `dvipsone` or `vtex` class  
options is declared but we only issue a warning in this case and set the “new” state  
to non-rotated. If all the pieces are in place, it sets the “new” state to rotated.  
Finally, it goes off to `\@foilhead`.

```

1011 \newcommand\foilhead{\new@rot@statefalse%           set state for the page
1012   \@ifnextchar[{\@foilhead}{\@foilhead[0\p@]}}
1013 \ifcompatibility
1014 \else
1015   \newcommand\rotatefoilhead{%

```

```

1016 \if@dvinfos
1017 \new@rot@statetrue
1018 \else\if@dvinfosone
1019 \new@rot@statetrue
1020 \else\if@vtex
1021 \new@rot@statetrue
1022 \else\if@pdftex
1023 \new@rot@statetrue
1024 \else
1025 \ClassWarningNoLine{FoilTex}{%
1026 Without the 'dvinfos', 'dvinfosone' or 'vtex' option \MessageBreak
1027 (when running LaTeX), rotation is not supported}
1028 \new@rot@statefalse
1029 \fi\fi\fi\fi
1030 \ifnextchar[{\@foilhead}{\@foilhead[0\p@]{}]}
1031 \fi

```

`\@foilhead` The new version of the `\@foilhead` macro now has more work to do. First, it clears the previous page so we start fresh on a new page. Next, it checks if we are supposed to rotate this page. If so, it sets the current page state to rotated and establishes the dimensions for the rotated page (`\@rot@dimens`, see Section ??). If not, it sets the current page state to non-rotated and establishes the non-rotated page dimensions (`\@defaultdimens`, see Section ??). Then it sets the font in large boldface, centers the title and adjusts the vertical spacing. We also wrap this header in a color group and reset to normal color so it doesn't get corrupted by other things.

```

1032 \def\@foilhead[#1]#2{\vfill\ejct
1033 \ifnew@rot@state
1034 \cur@rot@statetrue\@rot@dimens
1035 \if@pdftex\@rot@dimens@pdf\fi % add this if pdftex
1036 \else
1037 \cur@rot@statefalse\@defaultdimens
1038 \if@pdftex\@defaultdimens@pdf\fi % add this if pdftex
1039 \fi
1040 {\color@begingroup\normalcolor
1041 \reset@font\large\bfseries\centering#2\par\null\color@endgroup}%
1042 \advance\foilheadskip by #1 \vspace{\foilheadskip}
1043 \advance\foilheadskip by -#1}

```

`\@shipoutsetup` We do some trickery here to get the right things to happen at shipout to enable rotation. Namely, before we do any shipout, if rotation is in effect, we issue the `\foil@rot@start` (handled by `dvips`) and then do the shipout. This enables us to interact with perhaps other utilities that muck with these internals and make sure that the rotation stuff happens at exactly the right point. The trickery is standard stuff, save the old definition, and merge the saved definition with the new stuff added.

```

1044 %\let\old@shipoutsetup\@shipoutsetup
1045 %\def\@shipoutsetup{%
1046 % \ifcur@rot@state\foil@rot@start\fi
1047 % \old@shipoutsetup}

```

`\@beginarvi` Unfortunately, They changed the output routine so this old stuff above didn't  
`\foil@beginarvi` work anymore, which is why it is commented out. Below is a hack that resolves the problem but some of Them (the L<sup>A</sup>T<sub>E</sub>X3 team) didn't like it because it misuses the command `\@beginarvi`. We use it anyway. First check to see if They change things again in the future with `\CheckCommand*`. If so, this will warn the user (and so me). Next we hack in something to get the rotation effects we need. This is hacked further in 2.1.4 for `hyperref` interactions.

```

1048 \CheckCommand*\@beginarvi{%
1049   \unvbox \@beginarvi
1050   \global\let \@beginarvi \@empty}
1051 % the old definitions
1052 %\def \@beginarvi{%
1053 %  \ifcur@rot@state\foil@rot@start\fi
1054 %  \unvbox \@beginarvi
1055 %  %\global\let \@beginarvi \@empty
1056 %  \gdef\@beginarvi{\ifcur@rot@state\foil@rot@start\fi\@empty}
1057 %}
1058 \def\foil@beginarvi{%
1059   \ifcur@rot@state\foil@rot@start\fi
1060 }
1061 \def\@beginarvi{%
1062   \foil@beginarvi
1063   \unvbox \@beginarvi
1064   \gdef\@beginarvi{\foil@beginarvi\@empty}
1065 }

```

`\@outputpage` The more recommended fix follows. It really isn't very robust but it is what They recommended. Essentially, I check the old definition of `\@outputpage` (the one from L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>, 1995/06/01 patch level 3) and see if this has changed at all. If it has, then the user gets a warning to this effect. I then simply redefine it the way I want it based on this definition. All this does is provide some warning in case the official definition changed when I wasn't looking.

```

1066 %\CheckCommand*\@outputpage{%
1067 %\begingroup
1068 % \set@typeset@protect
1069 % \@shipoutsetup
1070 % \let \protect \noexpand
1071 % \shipout \vbox{%
1072 %   \set@typeset@protect
1073 %   \aftergroup\set@typeset@protect
1074 %   \@beginarvi
1075 %   \vskip \topmargin
1076 %   \moveright\@themargin \vbox {%
1077 %     \setbox\@tempboxa \vbox to\headheight{%
1078 %       \vfil
1079 %       \color@hbox
1080 %       \normalcolor
1081 %       \hb@xt@\textwidth {%
1082 %         \let \label \@gobble
1083 %         \let \index \@gobble
1084 %         \let \glossary \@gobble %% 21 Jun 91
1085 %         \@thehead

```



```

1086 %      }%
1087 %      \color@endbox
1088 %      }%                %% 22 Feb 87
1089 %      \dp\@tempboxa \z@
1090 %      \box\@tempboxa
1091 %      \vskip \headsep
1092 %      \box\@outputbox
1093 %      \baselineskip \footskip
1094 %      \color@hbox
1095 %      \normalcolor
1096 %      \hb@xt@\textwidth{%
1097 %      \let \label \@gobble
1098 %      \let \index \@gobble    %% 22 Feb 87
1099 %      \let \glossary \@gobble %% 21 Jun 91
1100 %      \@thefoot
1101 %      }%
1102 %      \color@endbox
1103 %      }%
1104 %      }%
1105 % \endgroup
1106 % \global \@colht \textheight
1107 % \stepcounter{page}%
1108 % \let\firstmark\botmark
1109 %}
1110 %\def\@outputpage{%
1111 %\begingroup
1112 % \set@typeset@protect
1113 % \@shipoutsetup
1114 % \let \protect \noexpand
1115 % \shipout \vbox{%
1116 %   \set@typeset@protect
1117 %   \aftergroup\set@typeset@protect
1118 %   \@beginndvi
1119 %   \ifcur@rot@state\foil@rot@start\fi %% added by for foils.cls
1120 %   \vskip \topmargin
1121 %   \moveright\@themargin \vbox {%
1122 %     \setbox\@tempboxa \vbox to\headheight{%
1123 %       \vfil
1124 %       \color@hbox
1125 %       \normalcolor
1126 %       \hb@xt@\textwidth {%
1127 %         \let \label \@gobble
1128 %         \let \index \@gobble
1129 %         \let \glossary \@gobble %% 21 Jun 91
1130 %         \@thehead
1131 %       }%
1132 %     \color@endbox
1133 %   }%                %% 22 Feb 87
1134 %   \dp\@tempboxa \z@
1135 %   \box\@tempboxa
1136 %   \vskip \headsep
1137 %   \box\@outputbox
1138 %   \baselineskip \footskip
1139 %   \color@hbox

```

```

1140 %      \normalcolor
1141 %      \hb@xt@\textwidth{%
1142 %          \let \label \@gobble
1143 %          \let \index \@gobble      %% 22 Feb 87
1144 %          \let \glossary \@gobble  %% 21 Jun 91
1145 %          \@thefoot
1146 %      }%
1147 %      \color@endbox
1148 %    }%
1149 %  }%
1150 % \endgroup
1151 % \global \@colht \textheight
1152 % \stepcounter{page}%
1153 % \let\firstmark\botmark
1154 %}

```

## 11.11 Theorem-like environments

The next few macros set up special environments for theorem-like structures. The unstarred forms are numbered; the starred forms are unnumbered. We use slanted fonts for all of these. User's can easily change this if they wish. Both the starred and unstarred are created with one simple `\newtheorem` declaration (similar to the non-floats of Section ??). We try to use as much of the default L<sup>A</sup>T<sub>E</sub>X stuff as possible here.

`\newtheorem` As in the standard definition, we have to deal with optional arguments to the `\@Othm` `\newtheorem` declaration. We set this up an extra level deep by intercepting the default arguments with `\@Othm` and `\@Nthm` and then passing the arguments down one level simultaneously to the new `\@Sthm` and the old `\@othm` and `\@nthm`. The `\@starthm` `\@Sthm` defines the starred name and the environment in terms of the `\@starthm`, `\@xstarthm` which again recursively calls subconstructs to deal with the second optional argument and which do the actual environment construction. This is very parallel to standard L<sup>A</sup>T<sub>E</sub>X. Notice that we put everything in slanted text.

```

1155 \def\newtheorem#1{\ifnextchar[{\@Othm{#1}}{\@Nthm{#1}}}
1156 \def\@Othm#1[#2]#3{\@Sthm{#1}{#3}\@othm{#1}[#2]{#3}}
1157 \def\@Nthm#1#2{\@Sthm{#1}{#2}\@nthm{#1}{#2}}
1158 \def\@Sthm#1#2{{\global\@namedef{#1*}{\@starthm{#2}}
1159   \global\@namedef{end#1*}{\@endtheorem}}}}
1160 \def\@starthm#1{\ifnextchar[{\@ystarthm{#1}}{\@xstarthm{#1}}}
1161 \def\@xstarthm#1{\@beginstartheorem{#1} \ignorespaces}
1162 \def\@ystarthm#1[#2]{\@opargbeginstartheorem{#1}{#2}\ignorespaces}
1163 \def\@begintheorem#1#2{\trivlist
1164   \item[\hskip\labelsep{\bfseries #1\ #2. }]\slshape}
1165 \def\@opargbegintheorem#1#2#3{\trivlist
1166   \item[\hskip\labelsep{\bfseries #1\ #2.\ [#3] }]\slshape}
1167 \def\@beginstartheorem#1{\trivlist
1168   \item[\hskip\labelsep{\bfseries #1. }]\slshape}
1169 \def\@opargbeginstartheorem#1#2{\trivlist
1170   \item[\hskip\labelsep{\bfseries #1.\ [#2] }]\slshape}

```

`Theorem` For convenience, we predefine a few of the more standard environments. We use  
`Lemma` up token space here so perhaps this will have to be disabled so the user can do  
`Corollary`  
`Proposition`  
`Definition`

this for themselves. Note that the names are UpperCased to avoid some conflicts with user definitions that might already be in place.

```
1171 \newtheorem{Theorem}{Theorem}
1172 \newtheorem{Lemma}{Lemma}
1173 \newtheorem{Corollary}{Corollary}
1174 \newtheorem{Proposition}{Proposition}
1175 \newtheorem{Definition}{Definition}
```

**Proof** Finally, we set up a default Proof environment, with a nifty little square box at the end (this typically would come from the `latexsym` package but we steal just what we need for this to work here.

```
1176 \newenvironment{Proof}{\begin{trivlist}\item[] {\bfseries Proof.}}{%
1177 \ifhmode\nolinebreak[4]~$\ProofBox$\else$\ProofBox$\fi \end{trivlist}}
1178 \DeclareMathSymbol\ProofBox{0}{flasy}{"32}
```

## 11.12 Boldface mathematics

`\bm` Happily, in the new L<sup>A</sup>T<sub>E</sub>X, this is all done much better, particularly, with font selection. What we do here is just define a simple macro for setting small pieces of mathematics in bold (italics) and entire equations. This is mostly for backward compatibility. Note that the `\bm` macro is now much more robust. It uses the `\mathpalette` to set the style of its contents in the style of its surrounding environment rather than in just `\textstyle` as was done in the earlier Foil<sub>T</sub>E<sub>X</sub>. There are two bold equation environments, a starred (unnumbered) form and the unstarred (numbered) form. These environments have their macros constructed explicitly, rather than with the `\newenvironment` declaration.

```
1179 \def\bm#1{\mathpalette\bmstyle{#1}}
1180 \def\bmstyle#1#2{\mbox{\boldmath$#1#2$}}
1181 \@namedef{boldequation*}{\boldmath$$}
1182 \@namedef{endboldequation*}{$$\global\@ignoretrue\unboldmath}
1183 \def\boldequation{\boldmath$$\refstepcounter{equation}}
1184 \def\endboldequation{\eqno\@eqnnum%
1185   $$\global\@ignoretrue\unboldmath}
1186 </package>
```

## 12 The class option files

In these subsections we simply do a dump of the code for the size class option files. There is nothing deep here going on. Mostly we set the font sizes for the different relative font scaling, and adjust some of the basic settings in each level for display skips and for top level lists. There are two things to note here. First, we have added some larger fonts (51pt) over what was directly available in the old version. Second, the list setting parameters are set differently in the new version but act exactly as they did before in compatibility mode.

New here in version 2.1.3 are definitions for the `\big` and related operators which are now scaled according to the default font size (with the exception of `shortform` where this is not needed). In base L<sup>A</sup>T<sub>E</sub>X, these are handled the same across the different point sizes (because those sizes varied so little). The numbers here are basically computed from the values in the base L<sup>A</sup>T<sub>E</sub>X. An alternative approach to this is the `exscale` package.

## 12.1 The 17pt option

```
1187 (*17pt)
1188 \def\normalsize{\@setfontsize\normalsize\@xvipt{22}}%
1189 \abovedisplayskip 20\p@ \@plus 3\p@ \@minus 4\p@
1190 \belowdisplayskip \abovedisplayskip
1191 \abovedisplayshortskip \z@ \@plus 2\p@
1192 \belowdisplayshortskip 4\p@ \@plus 2\p@ \@minus 2\p@
1193 \let\@listi\@listIb}
1194 \normalsize
1195
1196 \def\small{\@setfontsize\small\@xivpt{18}}%
1197 \abovedisplayskip 16\p@ \@plus 2\p@ \@minus 4\p@
1198 \belowdisplayskip \abovedisplayskip
1199 \abovedisplayshortskip \z@ \@plus 1\p@
1200 \belowdisplayshortskip 3\p@ \@plus 1\p@ \@minus 2\p@
1201 \let\@listi\@listIc}
1202
1203 \def\footnotesize{\@setfontsize\footnotesize\@xipt{15}}%
1204 \abovedisplayskip 13\p@ \@plus 2\p@ \@minus 4\p@
1205 \belowdisplayskip \abovedisplayskip
1206 \abovedisplayshortskip \z@ \@plus 1\p@
1207 \belowdisplayshortskip 2\p@ \@plus 1\p@ \@minus 1\p@
1208 \let\@listi\@listId}
1209
1210 \def\large{\@setfontsize\large\@xxpt\@xxvpt
1211 \abovedisplayskip 30\p@ \@plus 3\p@ \@minus 9\p@
1212 \belowdisplayskip \abovedisplayskip
1213 \abovedisplayshortskip \z@ \@plus 3\p@
1214 \belowdisplayshortskip 7\p@ \@plus 3\p@ \@minus 4\p@
1215 \let\@listi\@listIa}
1216
1217 \let\scriptsize=\footnotesize
1218 \let\tiny=\footnotesize
1219 \def\Large{\@setfontsize\Large\@xxvpt{32}\let\@listi\@listIa}
1220 \def\LARGE{\@setfontsize\LARGE\@xxxpt{38}\let\@listi\@listIa}
1221 \def\huge{\@setfontsize\huge\@xxxvpt{45}\let\@listi\@listIa}
1222 \def\Huge{\@setfontsize\Huge\@xlvipt{54}\let\@listi\@listIa}
1223
1224 \def\big#1{\hbox{\left#1\ vbox to14.5\p@{} \right.\n@space$}}
1225 \def\Big#1{\hbox{\left#1\ vbox to19.5\p@{} \right.\n@space$}}
1226 \def\bigg#1{\hbox{\left#1\ vbox to24.5\p@{} \right.\n@space$}}
1227 \def\Bigg#1{\hbox{\left#1\ vbox to30\p@{} \right.\n@space$}}
1228 </17pt>
```

## 12.2 The 20pt option

```
1229 (*20pt)
1230 \def\normalsize{\@setfontsize\normalsize\@xxpt\@xxvpt
1231 \abovedisplayskip 30\p@ \@plus 3\p@ \@minus 9\p@
1232 \belowdisplayskip \abovedisplayskip
1233 \abovedisplayshortskip \z@ \@plus 3\p@
1234 \belowdisplayshortskip 7\p@ \@plus 3\p@ \@minus 4\p@
1235 \let\@listi\@listIa}
1236 \normalsize
```

```

1237
1238 \def\small{\@setfontsize\small\@xvipt{22}%
1239 \abovedisplayskip 20\p@ \@plus 3\p@ \@minus 4\p@
1240 \belowdisplayskip \abovedisplayskip
1241 \abovedisplayshortskip \z@ \@plus 2\p@
1242 \belowdisplayshortskip 4\p@ \@plus 2\p@ \@minus 2\p@
1243 \let\@listi\@listIb}
1244
1245 \def\footnotesize{\@setfontsize\footnotesize\@xivpt{18}%
1246 \abovedisplayskip 16\p@ \@plus 2\p@ \@minus 4\p@
1247 \belowdisplayskip \abovedisplayskip
1248 \abovedisplayshortskip \z@ \@plus 1\p@
1249 \belowdisplayshortskip 3\p@ \@plus 1\p@ \@minus 2\p@
1250 \let\@listi\@listIc}
1251
1252 \def\scriptsize{\@setfontsize\scriptsize\@xiipt{15}%
1253 \if@compatibility\else\let\@listi\@listId\fi}
1254 \let\tiny=\scriptsize
1255 \def\large{\@setfontsize\large\@xxvpt{32}}
1256 \def\Large{\@setfontsize\Large\@xxxpt{38}}
1257 \def\LARGE{\@setfontsize\LARGE\@xxxvpt{45}}
1258 \def\huge{\@setfontsize\huge\@xliipt{54}}
1259 \if@compatibility
1260 \let\Huge=\huge
1261 \else
1262 \def\Huge{\@setfontsize\huge\@lipt{62}}
1263 \fi
1264
1265 \def\big#1{\hbox{\$left#1\ vbox to17\p@{} \right.\n@space$}}
1266 \def\Big#1{\hbox{\$left#1\ vbox to23\p@{} \right.\n@space$}}
1267 \def\bigg#1{\hbox{\$left#1\ vbox to27\p@{} \right.\n@space$}}
1268 \def\Bigg#1{\hbox{\$left#1\ vbox to35\p@{} \right.\n@space$}}
1269 </20pt>

```

### 12.3 The 25pt option

```

1270 (*25pt)
1271 \def\normalsize{\@setfontsize\normalsize\@xxvpt{32}%
1272 \abovedisplayskip 30\p@ \@plus 3\p@ \@minus 9\p@
1273 \belowdisplayskip \abovedisplayskip
1274 \abovedisplayshortskip \z@ \@plus 3\p@
1275 \belowdisplayshortskip 7\p@ \@plus 3\p@ \@minus 4\p@
1276 \let\@listi\@listIa}
1277 \normalsize
1278
1279 \def\small{\@setfontsize\small\@xxpt\@xxvpt
1280 \abovedisplayskip 30\p@ \@plus 3\p@ \@minus 9\p@
1281 \belowdisplayskip \abovedisplayskip
1282 \abovedisplayshortskip \z@ \@plus 3\p@
1283 \belowdisplayshortskip 7\p@ \@plus 3\p@ \@minus 4\p@
1284 \if@compatibility
1285 \let\@listi\@listIb
1286 \else
1287 \let\@listi\@listIa\fi
1288 }

```

```

1289
1290 \def\footnotesize{\@setfontsize\footnotesize\@xvipt{22}}%
1291 \abovedisplayskip 20\p@ \@plus 3\p@ \@minus 4\p@
1292 \belowdisplayskip \abovedisplayskip
1293 \abovedisplayshortskip \z@ \@plus 2\p@
1294 \belowdisplayshortskip 4\p@ \@plus 2\p@ \@minus 2\p@
1295 \let\@listi\@listIb}
1296
1297 \def\scriptsize{\@setfontsize\scriptsize\@xivpt{18}}%
1298 \ifcompatibility\else\let\@listi\@listIc\fi}
1299 \def\tiny{\@setfontsize\tiny\@xipt{15}}%
1300 \ifcompatibility\else\let\@listi\@listId\fi}
1301 \def\large{\@setfontsize\large\@xxxpt{38}}
1302 \def\Large{\@setfontsize\Large\@xxxvpt{45}}
1303 \def\LARGE{\@setfontsize\LARGE\@xliipt{54}}
1304 \ifcompatibility
1305 \let\huge=\LARGE
1306 \let\Huge=\LARGE
1307 \else
1308 \def\huge{\@setfontsize\huge\@lipt{62}}
1309 \let\Huge=\huge
1310 \fi
1311
1312 \def\big#1{\hbox{\$left#1\ vbox to21\p@{\}right.\n@space$}}
1313 \def\Big#1{\hbox{\$left#1\ vbox to29\p@{\}right.\n@space$}}
1314 \def\bigg#1{\hbox{\$left#1\ vbox to36\p@{\}right.\n@space$}}
1315 \def\Bigg#1{\hbox{\$left#1\ vbox to44\p@{\}right.\n@space$}}
1316 </25pt>

```

## 12.4 The 30pt option

```

1317 (*30pt)
1318 \def\normalsize{\@setfontsize\normalsize\@xxxpt{38}}%
1319 \abovedisplayskip 30\p@ \@plus 3\p@ \@minus 9\p@
1320 \belowdisplayskip \abovedisplayskip
1321 \abovedisplayshortskip \z@ \@plus 3\p@
1322 \belowdisplayshortskip 7\p@ \@plus 3\p@ \@minus 4\p@
1323 \let\@listi\@listIa}
1324 \normalsize
1325
1326 \def\small{\@setfontsize\small\@xxvpt{32}}%
1327 \abovedisplayskip 30\p@ \@plus 3\p@ \@minus 9\p@
1328 \belowdisplayskip \abovedisplayskip
1329 \abovedisplayshortskip \z@ \@plus 3\p@
1330 \belowdisplayshortskip 7\p@ \@plus 3\p@ \@minus 4\p@
1331 \ifcompatibility
1332 \let\@listi\@listIb
1333 \else
1334 \let\@listi\@listIa\fi
1335 }
1336
1337 \def\footnotesize{\@setfontsize\footnotesize\@xxpt\@xxvpt
1338 \abovedisplayskip 30\p@ \@plus 3\p@ \@minus 9\p@
1339 \belowdisplayskip \abovedisplayskip
1340 \abovedisplayshortskip \z@ \@plus 3\p@

```

```

1341 \belowdisplayskip 7\p@ \@plus 3\p@ \@minus 4\p@
1342 \ifcompatibility
1343 \let\@listi\@listIb
1344 \else
1345 \let\@listi\@listIa\fi
1346 }
1347
1348 \def\scriptsize{\@setfontsize\scriptsize\@xvipt{22}%
1349 \ifcompatibility\else\let\@listi\@listIb\fi}
1350 \def\tiny{\@setfontsize\tiny\@xivpt{18}%
1351 \ifcompatibility\else\let\@listi\@listIc\fi}
1352 \def\large{\@setfontsize\large\@xxxvpt{45}}
1353 \def\Large{\@setfontsize\Large\@xliipt{54}}
1354 \ifcompatibility
1355 \let\LARGE=\Large
1356 \let\huge=\Large
1357 \let\Huge=\Large
1358 \else
1359 \def\LARGE{\@setfontsize\LARGE\@lipt{62}}
1360 \let\huge=\LARGE
1361 \let\Huge=\LARGE
1362 \fi
1363
1364 \def\big#1{{\hbox{\$left#1\ vbox to25.5\p@}\right.\n@space$}}
1365 \def\Big#1{{\hbox{\$left#1\ vbox to34.5\p@}\right.\n@space$}}
1366 \def\bigg#1{{\hbox{\$left#1\ vbox to43.5\p@}\right.\n@space$}}
1367 \def\Bigg#1{{\hbox{\$left#1\ vbox to52.5\p@}\right.\n@space$}}
1368 </30pt>

```

## 12.5 The shortform option

In this version, we set `\normalsize` and hang all smaller sizes off of this. For larger sizes, we take a simple short cut. We are making no attempt to optimize most of this, just to scale the fonts to a much smaller relative size.

Finally, because we want to change `\foilhead` so that it doesn't force a page break, we redefine `\@foilhead` in a much more simple manner. This is done in `\AtBeginDocument` since this file is read before the definitions in `foils.cls`. (We also make a change to `\parskip` so that paragraphs are less separated.)

```

1369 (*short)
1370 \def\normalize{\@setfontsize\normalize\@xipt{15}}
1371 \abovedisplayskip 12\p@ \@plus 3\p@ \@minus 4\p@
1372 \belowdisplayskip \abovedisplayskip
1373 \abovedisplayshortskip \z@ \@plus 2\p@
1374 \belowdisplayshortskip 4\p@ \@plus 2\p@ \@minus 2\p@
1375 \let\@listi\@listId}
1376 \normalsize
1377
1378 \let\small\normalize
1379 \let\footnotesize\normalize
1380 \let\scriptsize=\footnotesize
1381 \let\tiny=\footnotesize
1382
1383 \def\large{\@setfontsize\large\@xivpt{18}\let\@listi\@listId}
1384 \def\Large{\@setfontsize\Large\@xvipt{22}\let\@listi\@listId}

```

```

1385 \def\LARGE{\setfontsize\LARGE\@xxpt{25}\let\@listi\@listId}
1386 \def\huge{\setfontsize\huge\@xxvpt{30}\let\@listi\@listId}
1387 \let\Huge\huge
1388
1389 \AtBeginDocument{
1390 \def\@foilhead[#1]#2{{\vspace{2em}\pagebreak[1]%
1391     \color@begingroup\normalcolor
1392     \reset@font\large\bfseries\centering#2\nopagebreak[4]%
1393     \par\null\color@endgroup}}%
1394 \setlength\parskip{4\p@ \@plus 4\p@ \@minus 4\p@}
1395 }
1396 </short>

```

## 13 Compatibility mode

We include here the code for generating the compatibility mode style file. This is modelled after the L<sup>A</sup>T<sub>E</sub>X `article.sty`.

```

1397 (*oldstyle)
1398 \obsoletefile{foils.cls}{foils.sty}
1399 \LoadClass{foils}
1400 </oldstyle>

```

## 14 Font definitions

Here starts everything that sets up font information. For almost everything we use a new font family. These names are essentially the standard names with an `f` prefix. We could probably get away with just overriding the standard ones but we don't really know what we're doing here and this seems to work. We begin with a short section that sets up the default font characteristics. We absolutely need to do the family definition (and at this early stage) to make sure that the default L<sup>A</sup>T<sub>E</sub>X stuff is not loaded. (The `\normalsize` declaration in the `foil\@ptsize.clo` files think these are the L<sup>A</sup>T<sub>E</sub>X defaults of `{OT1}{cmr}{m}{n}` and these don't come in a large enough size!). The other lines are not strictly needed but we add them for completeness.

```

1401 (*fonts)
1402 \def\f@encoding{OT1}
1403 \def\f@family{fcmss}
1404 \def\f@series{m}
1405 \def\f@shape{n}

```

### 14.1 Font macro utilities

Here we add a couple of short hand macros for declaring font shapes. These are blazently borrowed from a recent L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> release (clever of those people to come up with such nice shorthand). Note that we have to wrap this in some special category code changes (in a group) to get the parsing correct). We have two versions of the general font shape definition, one for OT1 encoding and one for the T1 encoding. We have another version for math families, one for substitution and a special *odd* one because CMR is used in both math and text mode (sometimes).



The last conditional test just makes it easier to implement the EC to DC font switch.

```

1406 \begingroup
1407 \nfss@catcodes
1408 \providecommand{\flt@family}[5]{%
1409   \DeclareFontShape{#1}{#2}{#3}{#4}
1410   {<12><14.4><17.28><20.74><24.88><29.86>
1411     <35.83><43.00><51.60> #5 }{}}
1412 \providecommand{\fltodd@family}[6]{%
1413   \DeclareFontShape{#1}{#2}{#3}{#4}
1414   {<12.1><14.5><17.38> #5
1415     <12><14.4><17.28><20.74><24.88><29.86><35.83><43.00><51.60> #6}{}}
1416 \providecommand{\flt@subfamily}[5]{%
1417   \DeclareFontShape{#1}{#2}{#3}{#4}{<->ssub * #5}{}}
1418 \providecommand{\fltEC@family}[5]{%
1419   \DeclareFontShape{#1}{#2}{#3}{#4}
1420   {<12><14.4><17.28><20.74><24.88><29.86>
1421     <35.83><43.00><51.60> genb * #5}{}}
1422 \providecommand{\fltmath@family}[6]{%
1423   \DeclareFontShape{#1}{#2}{#3}{#4}
1424   {<12.1><14.5><17.38> #5
1425     <20.74><24.88><29.86><35.83><43.00><51.60> #6}{}}
1426 \if@useDCfonts
1427 \def\EC{dc}
1428 \def\ECrm{dcr}
1429 \def\ECrb{dcb}
1430 \def\ECui{dcu}
1431 \else
1432 \def\EC{ec}
1433 \def\ECrm{ecrm}
1434 \def\ECrb{ecrb}
1435 \def\ECui{ecui}
1436 \fi

```

## 14.2 The font family and shape declarations: OT1

Mostly we just set up only large versions of the fonts. We had to do some non-obvious things here in the smaller versions. See Subsection ?? for more information (this will explain the 12.1, 14.5 and 17.38 sizes below instead of the expected 12.0, 14.4 and 17.28). We first load the font family and shape information for the standard Computer Modern text fonts. We start with Roman (family `fcmr`).

```
1437 \DeclareFontFamily{OT1}{fcmr}{}

```

First we make a shape declaration for medium/normal. Note that we are a bit redundant here on the smaller point sizes. That is so that the math sizes and the scaled text sizes can work together without generating too many error messages. See also Subsection ??.

```
1438 \fltodd@family{OT1}{fcmr}{m}{n}   {cmr7}{cmr10}

```

Then we make one for medium/italics. (Slanted is handled by a substitution given later to the default family `fcms`.)

```
1439 \flt@family{OT1}{fcmr}{m}{it}    {cmti10}

```

We really should have a small caps version of cmss, but no such font is default, so we leave it as is.

```
1440 \flt@family{OT1}{fcmr}{m}{sc}    {cmcsc10}
```

Now, we add one for bold-extended.

```
1441 \flt@family{OT1}{fcmr}{bx}{n}    {cmbx10}
```

Next, we add some for bold-extended in italics and slanted. We don't expect these to get called directly, but as substitution fonts for sans serif versions.

```
1442 \flt@family{OT1}{fcmr}{bx}{sl}   {cmbxsl10}
```

As in the standard L<sup>A</sup>T<sub>E</sub>X, we use the upright shape font, essentially only for the `\pounds` symbol.

```
1443 \flt@family{OT1}{fcmr}{m}{ui}    {cmu10}
```

```
1444 % Finally, we fill in a few missing gaps with substitution fonts.
```

```
1445 \flt@subfamily{OT1}{fcmr}{m}{sl}  {fcmss/m/sl}
```

```
1446 \flt@subfamily{OT1}{fcmr}{b}{n}   {fcmr/bx/n}
```

```
1447 \flt@subfamily{OT1}{fcmr}{bx}{it} {fcmr/bx/sl}
```

Now we set up the essential stuff for the default family, San Serif (`fcmss`). Please consult pages 201–202 of [?] for more information about the use of `\fontdimen` stuff here. Essentially, we are allowing more inter-word space stretching, to compensate for the lack of hyphenation.

```
1448 \DeclareFontFamily{OT1}{fcmss}{\fontdimen3\font=1.7\fontdimen3\font}
```

First we make a shape declaration for medium/normal.

```
1449 \flt@family{OT1}{fcmss}{m}{n}    {cmss10}
```

Here is the slanted version.

```
1450 \flt@family{OT1}{fcmss}{m}{sl}   {cmssi10}
```

I don't know why this is here, but it is analogous to what is in the standard sets so we leave it in, just rescale the sizes. This is semi-bold condensed (or is that demi-bold condensed?).

```
1451 \flt@family{OT1}{fcmss}{sbc}{n}   {cmssdc10}
```

Finally, we get to the bold versions. There really is a bold extended sans serif so we point off to that.

```
1452 \flt@family{OT1}{fcmss}{bx}{n}   {cmssbx10}
```

Here are all the substitution fonts. Sans serif italics is not a standard font so we substitute roman italics. That's OK, because we will use slanted for emphasize anyway and I think user's expect roman italics.

```
1453 \flt@subfamily{OT1}{fcmss}{m}{it} {fcmr/m/it}
```

For small-caps, we substitute the roman small caps, which is what I think most users will expect and because we don't really have a small caps, sans serif.

```
1454 \flt@subfamily{OT1}{fcmss}{m}{sc} {fcmr/m/sc}
```

We again use the roman upright for the `\pounds` symbol.

```
1455 \flt@subfamily{OT1}{fcmss}{m}{ui} {fcmr/m/ui}
```

There is no plain bold, consequently, we substitute the bold extended. Finally, if someone asks for slanted or italics in bold extended, since we don't have either of these we substitute the roman counter parts. It seemed that if the user was in either bold extended (or italics) and wanted to italicize (or embolden), then they should see some change. From above, the `fcmr/bx/it` is replaced by `fcmr/bx/sl`

so this becomes our complete substitute for bold italics sans serif. We do these latter substitutions with a warning, so the user knows what happens and it doesn't come as a complete surprise.

```
1456 \flt@subfamily{OT1}{fcmss}{b}{n} {fcmss/bx/n}
1457 \flt@subfamily{OT1}{fcmss}{bx}{sl}{fcmr/bx/sl}
1458 \flt@subfamily{OT1}{fcmss}{bx}{it}{fcmr/bx/it}
```

Next we add the typewriter font (fcmstt). This is short and sweet. We set up for medium normal and slanted and everything else is a substitution.

```
1459 \DeclareFontFamily{OT1}{fcmstt}{\hyphenchar\font\m@ne}
1460 \flt@family{OT1}{fcmstt}{m}{n} {cmtt10}
1461 \flt@family{OT1}{fcmstt}{m}{sl} {cmsl10}
1462 \flt@subfamily{OT1}{fcmstt}{m}{it} {fcmstt/m/sl}
1463 \flt@subfamily{OT1}{fcmstt}{bx}{n} {fcmstt/m/n}
1464 \flt@subfamily{OT1}{fcmstt}{bx}{it}{fcmstt/m/it}
1465 \flt@subfamily{OT1}{fcmstt}{bx}{sl}{fcmstt/m/sl}
```

### 14.3 The font family and shape declarations: T1

Now we do the same for the EC font encoding. This is a bit tricky since we want to support choices between large design sizes and scaled fonts and choices between EC and old DC fonts. This has not been extensively tested but it seems to work and is logically consistent with the stuff from the LaTeX distribution, up to some changes to be consistent with how  $\text{Foil}_{\text{TeX}}$  dealt with the old versions of DC fonts. Where different, I've left  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X} 2_{\varepsilon}$ 's model as a comment. Feel free to switch if you want. We make no additional comments throughout the rest of these part.

```
1466 \DeclareFontFamily{T1}{fcmr}{}
1467 \if@magscaleECfonts
1468 \flt@family{T1}{fcmr}{m}{n} {\ECrm 1000}
1469 \flt@family{T1}{fcmr}{m}{it} {\EC ti1000}
1470 \flt@family{T1}{fcmr}{m}{sc} {\EC cc1000}
1471 \flt@family{T1}{fcmr}{bx}{n} {\EC bx1000}
1472 \flt@family{T1}{fcmr}{bx}{sl} {\EC bl1000}
1473 \flt@family{T1}{fcmr}{m}{ui} {\ECui 1000}
1474 \else
1475 \fltEC@family{T1}{fcmr}{m}{n} {\ECrm}
1476 \fltEC@family{T1}{fcmr}{m}{it} {\EC ti}
1477 \fltEC@family{T1}{fcmr}{m}{sc} {\EC cc}
1478 \fltEC@family{T1}{fcmr}{bx}{n} {\EC bx}
1479 \fltEC@family{T1}{fcmr}{bx}{sl} {\EC bl}
1480 \fltEC@family{T1}{fcmr}{m}{ui} {\ECui}
1481 \fi
1482 \flt@subfamily{T1}{fcmr}{m}{sl} {fcmss/m/sl}
1483 %\if@magscaleECfonts
1484 % \flt@family{T1}{fcmr}{m}{sl} {\EC sl1000}
1485 %\else
1486 % \fltEC@family{T1}{fcmr}{m}{sl} {\EC sl}
1487 %\fi
1488 \flt@subfamily{T1}{fcmr}{b}{n} {fcmr/bx/n}
1489 \flt@subfamily{T1}{fcmr}{bx}{it} {fcmr/bx/sl}
1490 \DeclareFontFamily{T1}{fcmss}{\fontdimen3\font=1.7\fontdimen3\font}
1491 \if@magscaleECfonts
1492 \flt@family{T1}{fcmss}{m}{n} {\EC ss1000}
```

```

1493 \flt@family{T1}{fcmss}{m}{sl} {\EC si1000}
1494 \flt@family{T1}{fcmss}{bx}{n} {\EC sx1000}
1495 \else
1496 \fltEC@family{T1}{fcmss}{m}{n} {\EC ss}
1497 \fltEC@family{T1}{fcmss}{m}{sl} {\EC si}
1498 \fltEC@family{T1}{fcmss}{bx}{n} {\EC sx}
1499 \fi
1500 \flt@family{T1}{fcmss}{sbc}{n} {\EC ssdc10}
1501 \flt@subfamily{T1}{fcmss}{m}{it} {fcmr/m/it}
1502 %\if@magscaleECfonts
1503 % \flt@family{T1}{fcmss}{m}{it} {\EC si1000}
1504 %\else
1505 % \fltEC@family{T1}{fcmss}{m}{it} {\EC si}
1506 %\fi
1507 \flt@subfamily{T1}{fcmss}{m}{sc} {fcmr/m/sc}
1508 \flt@subfamily{T1}{fcmss}{m}{ui} {fcmr/m/ui}
1509 \flt@subfamily{T1}{fcmss}{b}{n} {fcmss/bx/n}
1510 \flt@subfamily{T1}{fcmss}{bx}{it} {fcmr/bx/it}
1511 %\if@magscaleECfonts
1512 % \flt@family{T1}{fcmss}{bx}{it} {\EC so1000}
1513 %\else
1514 % \fltEC@family{T1}{fcmss}{bx}{it}{\EC so}
1515 %\fi
1516 \flt@subfamily{T1}{fcmss}{bx}{sl} {fcmr/bx/sl}
1517 %\if@magscaleECfonts
1518 % \flt@family{T1}{fcmss}{bx}{sl} {\EC so1000}
1519 %\else
1520 % \fltEC@family{T1}{fcmss}{bx}{sl}{\EC so}
1521 %\fi
1522 \DeclareFontFamily{T1}{fcmtt}{\hyphenchar\font\m@ne}
1523 \if@magscaleECfonts
1524 \flt@family{T1}{fcmtt}{m}{n} {\EC tt1000}
1525 \flt@family{T1}{fcmtt}{m}{sl} {\EC st1000}
1526 \else
1527 \fltEC@family{T1}{fcmtt}{m}{n} {\EC tt}
1528 \fltEC@family{T1}{fcmtt}{m}{sl} {\EC st}
1529 \fi
1530 \flt@subfamily{T1}{fcmtt}{m}{it} {fcmtt/m/sl}
1531 %\if@magscaleECfonts
1532 % \flt@family{T1}{fcmtt}{m}{it} {\EC it1000}
1533 %\else
1534 % \fltEC@family{T1}{fcmtt}{m}{it} {\EC it}
1535 %\fi
1536 \flt@subfamily{T1}{fcmtt}{bx}{n} {fcmtt/m/n}
1537 \flt@subfamily{T1}{fcmtt}{bx}{it} {fcmtt/m/it}
1538 \flt@subfamily{T1}{fcmtt}{bx}{sl} {fcmtt/m/sl}
1539 %%%%%%%%% DO WE NEED TO DO THE TS1 COMPANION FONTS???? %%%%%%%%%

```

## 14.4 The font family and shape declarations: OM\*

Of course, we still haven't dealt directly with any of the math fonts. We start with math italics. Note again the strange point sizes in the smaller fonts.

```

1540 \DeclareFontFamily{OML}{fcmml}{\skewchar\font'177}
1541 \fltmath@family{OML}{fcmml}{m}{it} {cmml7}{cmml10}

```

```

1542 \fltmath@family{OML}{fcmm}{b}{it} {cmmib7}{cmmib10}
1543 \flt@subfamily{OML}{fcmm}{bx}{it} {fcmm/b/it}

```

Next we add the standard symbol fonts in normal and bold.

```

1544 \DeclareFontFamily{OMS}{fcmsy}{\skewchar\font'60}
1545 \fltmath@family{OMS}{fcmsy}{m}{n} {cmsy7}{cmsy10}
1546 \fltmath@family{OMS}{fcmsy}{b}{n} {cmbsy7}{cmbsy10}
1547 \flt@subfamily{OMS}{fcmsy}{bx}{n} {fcmsy/b/n}

```

The December 1994 release added stuff for cmr math symbols, so we have to do the same here to avoid warning messages. We add a few more than what is in the standard L<sup>A</sup>T<sub>E</sub>X because we don't like these warning messages.

```

1548 \DeclareFontFamily{OML}{fcms}{\skewchar\font'177}
1549 \flt@subfamily{OML}{fcms}{m}{n} {fcmm/m/it}
1550 \flt@subfamily{OML}{fcms}{m}{it} {fcmm/m/it}
1551 \flt@subfamily{OML}{fcms}{m}{sl} {fcmm/m/it}
1552 \flt@subfamily{OML}{fcms}{m}{sc} {fcmm/m/it}
1553 \flt@subfamily{OML}{fcms}{bx}{n} {fcmm/m/it}
1554 \flt@subfamily{OML}{fcms}{b}{n} {fcmm/m/it}
1555 \flt@subfamily{OML}{fcms}{bx}{sl}{fcmm/m/it}
1556 \flt@subfamily{OML}{fcms}{bx}{it}{fcmm/m/it}
1557 \DeclareFontFamily{OMS}{fcms}{\skewchar\font'60}
1558 \flt@subfamily{OMS}{fcms}{m}{n} {fcmsy/m/n}
1559 \flt@subfamily{OMS}{fcms}{m}{it} {fcmsy/m/n}
1560 \flt@subfamily{OMS}{fcms}{m}{sl} {fcmsy/m/n}
1561 \flt@subfamily{OMS}{fcms}{m}{sc} {fcmsy/m/n}
1562 \flt@subfamily{OMS}{fcms}{bx}{n} {fcmsy/b/n}
1563 \flt@subfamily{OMS}{fcms}{b}{n} {fcmsy/b/n}
1564 \flt@subfamily{OMS}{fcms}{bx}{sl}{fcmsy/b/n}
1565 \flt@subfamily{OMS}{fcms}{bx}{it}{fcmsy/b/n}
1566 \DeclareFontFamily{OML}{fcmr}{\skewchar\font'177}
1567 \flt@subfamily{OML}{fcmr}{m}{n} {fcmm/m/it}
1568 \DeclareFontFamily{OML}{fcmtt}{\skewchar\font'177}
1569 \flt@subfamily{OML}{fcmtt}{m}{n} {fcmm/m/it}
1570 \DeclareFontFamily{OMS}{fcmr}{\skewchar\font'60}
1571 \flt@subfamily{OMS}{fcmr}{m}{n} {fcmsy/m/n}
1572 \DeclareFontFamily{OMS}{fcmtt}{\skewchar\font'60}
1573 \flt@subfamily{OMS}{fcmtt}{m}{n} {fcmsy/m/n}

```

Don't forget the extended symbol font for delimiters and the like.

```

1574 \DeclareFontFamily{OMX}{fcMex}{}{}
1575 \fltmath@family{OMX}{fcMex}{m}{n} {cmex7}{cmex10}

```

We were going to add one for a new Foil<sup>T</sup><sub>E</sub>X-L<sup>A</sup>T<sub>E</sub>X symbol font (`flasy`) but decided that was a bit much. Instead, we just set up the `lasy` font family and modify its parameters here. In this way, if the user specifies `\usepackage{latexsym}` the default `Ulasylfd` is *not* loaded and the sizes don't get overrun. Also, we avoid having to expressly define all the required symbols. We do define a symbol font (`flasy`) however so we can use it for the closing box at the end of proofs.

```

1576 \DeclareFontFamily{U}{lasy}{}
1577 \fltmath@family{U}{lasy}{m}{n} {lasy7}{lasy10}
1578 \flt@family{U}{lasy}{b}{n} {lasyb10}
1579 \endgroup % end of nfss@catcodes group
1580 \DeclareSymbolFont{flasy}{U}{lasy}{m}{n}

```

## 14.5 The font selection mechanisms

We've got all the font family and shape declaration tables set up. Now we configure the font selection mechanism for Foil<sub>TEX</sub>. First we define the defaults.

```
1581 \def\rmdefault{fcmr}
1582 \def\sfdefault{fcmss}
1583 \def\ttdefault{fcmtt}
1584 \def\itdefault{it}
1585 \def\sldefault{sl}
1586 \def\bfdefault{bx}
```

This next definition finally sets up the sans serif as the default family.

```
1587 \renewcommand\familydefault{\sfdefault}
```

Next we set up the old font changing commands and the ones used in math (except small caps and slanted which are prohibited in math). Notice here that (in contrast to SL<sub>TEX</sub>) the `\rm` is still roman! Also, we replace the `\em` declaration so that it switches between the upright shape and the *slanted* shape.

```
1588 \DeclareOldFontCommand{\rm}{\normalfont\rmfamily}{\mathrm}
1589 \DeclareOldFontCommand{\sf}{\normalfont\sffamily}{\mathsf}
1590 \DeclareOldFontCommand{\tt}{\normalfont\ttfamily}{\mathtt}
1591 \DeclareOldFontCommand{\bf}{\normalfont\bfseries}{\mathbf}
1592 \DeclareOldFontCommand{\it}{\normalfont\itshape}{\mathit}
1593 \DeclareOldFontCommand{\sl}{\normalfont\slshape}{\@nomath\sl}
1594 \DeclareOldFontCommand{\sc}{\normalfont\scshape}{\@nomath\sc}
1595 \DeclareRobustCommand\em{\@nomath\em \ifdim \fontdimen\@ne\font >\z@
1596     \upshape \else \slshape \fi}
```

## 14.6 Math and symbol fonts

We need to replace all the standard symbol, operator, letter and large symbol fonts with our new font families as declared above in Subsection ???. We do this for both normal and bold equations.

```
1597 \SetSymbolFont{operators}{normal}{OT1}{fcmr}{m}{n}
1598 \SetSymbolFont{letters}{normal}{OML}{fcmr}{m}{it}
1599 \SetSymbolFont{symbols}{normal}{OMS}{fcmss}{m}{n}
1600 \SetSymbolFont{largesymbols}{normal}{OMX}{fcmex}{m}{n}
1601 \SetSymbolFont{operators}{bold}{OT1}{fcmr}{bx}{n}
1602 \SetSymbolFont{letters}{bold}{OML}{fcmr}{b}{it}
1603 \SetSymbolFont{symbols}{bold}{OMS}{fcmss}{b}{n}
1604 \SetSymbolFont{largesymbols}{bold}{OMX}{fcmex}{m}{n}
```

We also need to set up the math alphabets for the font change commands and declarations in math mode. Note that we expressly set the math fonts to roman unless expressly asked for with `\mathsf` or `\mathtt`. All the others (`\mathbf` and `\mathit`, along with `\mathrm`) yield the roman (serif) counterpart. This is in contrast to what we do in text.

```
1605 \DeclareMathAlphabet{\mathrm}{OT1}{fcmr}{m}{n}
1606 \DeclareMathAlphabet{\mathbf}{OT1}{fcmr}{bx}{n}
1607 \DeclareMathAlphabet{\mathsf}{OT1}{fcmss}{m}{n}
1608 \DeclareMathAlphabet{\mathit}{OT1}{fcmr}{m}{it}
1609 \DeclareMathAlphabet{\mathtt}{OT1}{fcmtt}{m}{n}
```

Here are a few commands for caligraphic and math italics fonts:

```

1610 \DeclareRobustCommand*\cal{\@fontswitch{\relax}{\mathcal}}
1611 \DeclareRobustCommand*\mit{\@fontswitch{\relax}{\mathnormal}}

```

Now we get to the nub of the subtle issue of font point sizes. The natural thing to want to do (and was easy to do in OFSS) was the following. First determine the font (with natural point size) you want, determine mag-scaling needed to get this to the approximate point size desired and hard-code this as exactly equal. So, we could say that a 12pt version of a 7pt font was just scaled by magstep 3. This was in spite of the fact that this was more likely to be a 12.1pt font. In NFSS, the desired point size and the design size are used to compute the scaling desired so a declaration like 12pt scaling of 7pt font would require a non-standard magnification (and so drivers would either have to generate a whole new library of fonts, or scale existing fonts or L<sup>A</sup>T<sub>E</sub>X would have to scream out error messages about font substitutions.

This could be avoided if we simply used scaled versions of just 10pt fonts, but we found in the earlier Foil<sub>T</sub>E<sub>X</sub> that it looked much better in math mode to try to maintain as much of the relative scaling of fonts as was in Knuth's original design, namely 10pt (design-size) font should have a 7pt (design-size) exponent and 5pt super-exponent. In Foil<sub>T</sub>E<sub>X</sub>, we compromise a little on this and try to force (as can be seen from the font shape declarations above) scaled versions of 7pt fonts for exponents and smaller scaled versions of 7pt for super-exponents. But of course, this means that the math size for this needs to reflect this as much as possible (hence the 12.1pt version of 7pt fonts). On the other hand, some text fonts that also play a role in math mode (like roman) need to have their corresponding 12pt text versions (in `\tiny`, for example). That's why some of these fonts have size information for 12.1pt (`cmr7`) and 12pt (`cmr10`).

Consequently, we declare some tokens for the small math sizes as 12.1, 14.5 and 17.38 and then set the math sizes for the various point sizes. We also stick to the principle that no font should be smaller than 12pt so this limits what we can do in exponents and the like. We add one for really big fonts but only if we are not running in compatibility mode. Somewhere at sometime I wanted these really big stuff and so here it is now.

```

1612 \newcommand\@xii@ipt{12.1}
1613 \newcommand\@xiv@vpt{14.5}
1614 \newcommand\@xvii@iiipt{17.38}
1615 \newcommand\@xxxpt{29.86}
1616 \newcommand\@xxxvpt{35.83}
1617 \newcommand\@xliiipt{43}
1618 \newcommand\@lipt{51.60}
1619 \DeclareMathSizes{\@xii@ipt}{\@xii@ipt}{\@xii@ipt}{\@xii@ipt}
1620 \DeclareMathSizes{\@xiv@vpt}{\@xiv@vpt}{\@xii@ipt}{\@xii@ipt}
1621 \DeclareMathSizes{\@xvii@iiipt}{\@xvii@iiipt}{\@xii@ipt}{\@xii@ipt}
1622 \DeclareMathSizes{\@xxxpt}{\@xxxpt}{\@xiv@vpt}{\@xiv@vpt}
1623 \DeclareMathSizes{\@xxvpt}{\@xxvpt}{\@xvii@iiipt}{\@xiv@vpt}
1624 \DeclareMathSizes{\@xxxpt}{\@xxxpt}{\@xxxpt}{\@xvii@iiipt}
1625 \DeclareMathSizes{\@xxxvpt}{\@xxxvpt}{\@xxvpt}{\@xxxpt}
1626 \DeclareMathSizes{\@xliiipt}{\@xliiipt}{\@xxxpt}{\@xxvpt}
1627 \ifcompatibility\else
1628 \DeclareMathSizes{\@lipt}{\@lipt}{\@xxxvpt}{\@xxxpt}
1629 \fi

```

Finally, we have to deal with the picture environment fonts (circle and line). These seem to be broken no matter what I do. I liked the fatter lines that I got with the

magscaled versions in the old Foil $\TeX$ , but it seemed to be very hard to convert user's pictures from  $\LaTeX$  to Foil $\TeX$ . So, in the new version we don't scale and in compatibility mode, we do scale. In either case, it's easy to generate pictures that just don't work!

```
1630 \if@compatibility
1631   \font\tencirc=lcircle10 scaled \magstep4
1632   \font\tencircw=lcirclew10 scaled \magstep4
1633   \font\tenln=line10 scaled \magstep4
1634   \font\tenlnw=linew10 scaled \magstep4
1635 \else
1636   \font\tencirc=lcircle10
1637   \font\tencircw=lcirclew10
1638   \font\tenln=line10
1639   \font\tenlnw=linew10
1640 \fi
1641 \end{font}
```

## References

- [1] Michel Goossens, Frank Mittelbach and Alexander Samarin, *The  $\LaTeX$  Companion*, Addison-Wesley, Reading, Massachusetts, 1994.
- [2] Donald Knuth, *The  $\TeX$ book*, Addison-Wesley, Reading, Massachusetts, 1983, revised in 1993.
- [3] Leslie Lamport,  *$\LaTeX$ : A Document Preparation System*, 2nd ed., Addison-Wesley, Reading, Massachusetts, 1994.